Digital Signal Processing

UNIT-01

Signal:- Any physical quantity vary with time / space and have two or more independent variables and that carries some information.

Ex: 1) Speech signal : Used in telephone, radio

2) Biomedical signal : ECG , MRI scan, EEG , city scan...

3) Sound signal : Music, .mp3's

4) Video signal : 3D , Image signal : 2D

5) Radon signal : Used to determine the range of target.


Signal Processing:- To extract useful information carried out by a signal.

⇒ It is concerned with the mathematical representation of a signal and the algorithmic operations carried out on it to extract the information present.

Signal Processing
- → Analog signal Processing (ASP)
- → Digital signal Processing (DSP)
- → Mixed signal processing (ASP + DSP)

Analog Signal Processing:-


Processing of analog signals to extract / modify to get meaningful information is said to be ASP.



Digital Signal Processing:-

Processing of digital signals inorder to analyze / extract / modify to get meaningful info is said to be DSP.

Scanned by CamScanner



Advantages of DSP:-

1. **Accuracy**: No. of bits used to represent the signal samples and the coefficients describing the processing operation.

   Accuracy ↑ as no. of bits to represent a given sample also ↑

2. **Flexibility**: DSP systems can be programmed / reprogrammed to perform variety of functions without modifying the hardware.

3. **Drift**:- DSP systems have no drift in performance with age / temperature.

4. **Adaptability**:- It can adopt to characteristics of the i/p or the processing task changes.

5. **Reproducability**: Identical performance from a DSP system is obtained since there are no variations due to component tolerance.

⇒ Copy / reproduce several times over without any degradation in the signal quality.

6. **Multiplexing**: Time sharing of digital signal processor.

⇒ Digital processing allows the sharing of a given processor, among a no. of signals by time sharing, so that we can reduce the cost of processing per signal.

Scanned by CamScanner

7. Data logging: Signals are stored for indefinitely without any loss of information.

8. Low frequency capability: DSP can handle lower frequency signal very efficiently

⇒ ASP can also handles very low frequency signal but with very large capacitors & inductors.


Disadvantages of DSP:-

1. Increase system complexibty: It requires preprocessing units like ADC, DAC

2. Speed & cost: Speed of ASP > Speed of DSP

cost of DSP ↑ as the no. of bits required to implemen the signal ↑

3. Finite word length:



Applications of DSP:-

Space, Medical: ECG signal analysis, CT Scan, MRI scan, ultra sound, Diagnostic imaging.

Commercial: Movie special effects, Video conferencing


Telephone: Voice, filtering

Military: Radon signaling, Sonar, missile's, communications.


Scientific: Earthquake recording, spectral analysis.

Scanned by CamScanner


Analog to Digital Converter (ADC):-



Ex:



① Sampler





$n=0 \Rightarrow t=0$

$n=1 \Rightarrow t=1Ts$

$n=2 \Rightarrow t=2Ts$

$n=3 \Rightarrow t=3Ts$





CACT signal

$n=1.5 \Rightarrow x[n]$ = undefined but not zero.

$x[n] = \{3.1, 2.2, 1.4, 1.2, 1.3, 2.2, 3, 3.2, 2.8\}$ ↑

② Quantizer

Quantizer $\Rightarrow$ Quantizer levels $\{1, 1.5, 2, 2.5, 3\}$ (5 levels)

↓

It will assign the input sequence samples to its nearest quantization levels.


i/p of quantizer $x[n] = \{3.1, 2.2, 1.4, 1.2, 1.3, 2.2, 3, 3.2, 2.8\}$ ↑

o/p of quantizer $x[n] = \{3, 2, 1.5, 1, 1.5, 2, 3, 3, 3\}$ ↑

Both discrete in time & Amplitude.

Scanned by CamScanner

③ Encoder



i/p of encoder $x[n] = \{3, 2, 1.5, 1, 1.5, 2, 3, 3, 3\}$

$(3)_{10} = (11)_2$

$(2)_{10} = (10)_2$

$(1.5)_{10} = (01.10)_2$

$(1)_{10} = (01)_2$

$(1.5)_{10} = (01.10)_2$

2 | 3 → 1
2 | 2 → 0
2 | 1 → 1


$(1.5)_{10} = 01.10$

$1_{10} = 01_2$

$0.5 \times 2 = 1$	Integer	Fraction
	1	0

Output : {11 10 01.10 01 0110 10 11 11 11}

Overall steps:-



Basic operations on discrete time sequence /signals:-

1. Signal Addition — $z[n] = x[n] + y[n]$
2. Signal multiplication — $z[n] = x[n] \cdot y[n]$
3. Scalar Addition — $y[n] = k + x[n]$
4. Scalar multiplication — $y[n] = k \cdot x[n]$

Scanned by CamScanner

Transformation of independent Variable (time):

1. Time shifting
2. Time Scaling → Decimation in time (Compression)
   → Interpolation in time (Expansion)
3. Time reversal


① Time Shifting:- $x[n] \longrightarrow x[n \pm n_0]$

if n_0 → +ve ⇒ right shift = $x[n+n_0]$ Delayed version of $x[n]$


→ -ve ⇒ Left shift = $x[n+n_0]$ Advanced version of $x[n]$

$y[n] = x[n \pm n_0]$ → Advancement / → Delay

Ex:-




$x[n] = \{1, 2, 3, 4, 5, 6, 7\}$ (↑ at 4)



Delay (Right Shif)


$n-2 \Rightarrow n = +2$




Advancement (Left Shift)

$n+2 = 0 \Rightarrow n = -2$


Ex: $x[n] = \{1, -2, -5, 2, 1, 1.5\}$ draw for $x[n+3]$, $x[n-2]$





$n+3 = 0 \Rightarrow n = -3$

Advanced by 3 units



$n-2 = 0 \Rightarrow n = 2$

Delayed by 2 units

Scanned by CamScanner

② Time Scaling :-

→ Decimation (Discarding s/g samples)

→ Interpolation (Inserting s/g samples)

- → 0 interpolation
- → 1 unity interpolation
- → Average interpolation

$= \frac{\text{Area of } x[n]}{\text{Samples in } x[n]}$

$\alpha > 1$ - Decimation

$(\alpha-1)$ samples get discarded


$\alpha < 1$ = Interpolation

$(\alpha-1)$ samples get added.

* Decimation of discrete time sequence will leads to loss of signal information.

Ex:- $x[n] = \{1, 2, 3, 4, 5\}$ (↑ at 0)

$x[2n] = \{1, 3, 5\}$ (↑ at 0)



$x[n] = 1, \ n=0$

$= 2, \ n=1$

$= 3, \ n=2$

$= 4, \ n=3$

$= 5, \ n=4$


$\frac{0}{2} = 0 \rightarrow$ int

$\frac{1}{2} = 0.5$

$\frac{2}{2} = 1 \rightarrow$ int

$\frac{3}{2} = 1.5$

$\frac{4}{2} = 2 \rightarrow$ int



Decimation:

$x[n] = \{1, 2, 3, 4, 5\} \Rightarrow x[2n] = \{1, 3, 5\}$

$x[n] = \{1, -6, 2, -3, 7, 9, 12\} \Rightarrow x[3n] = \{1, -3, 12\}$

$x[n] = \{1, 2, 3, 4, 5, 6, 7, 8, 9, 6, 7, 5, 4, 3, 2, 1, 1\} \Rightarrow x[4n] = \{1, 5, 9, 4, 1\}$

Interpolation:-

$x[n] = \{1, 2, 3, 4, 5\} \Rightarrow x\left[\frac{n}{2}\right] = \{1, 0, 2, 0, 3, 0, 4, 0, 5\}$ (↑ at 1 and at 0)

* By interpolation we don't lose any info, it is an expansion/ insertion of information.

Scanned by CamScanner

Take $x[n] = \{1, 2, 8, 4, 6\}$

(i) $\{1, 2, 8, 4, 6\} \xrightarrow{\text{Decimated by 2}} \{1, 8, 6\}$ (i.e $n \to 2n$) $\xrightarrow{\text{Interpolated by 2}} \{1, 0, 8, 0, 6\}$ ($n \to \frac{n}{2}$)

(ii) $\{1, 2, 8, 4, 6\} \xrightarrow{\text{Interpolation}} \{1, 0, 2, 0, 8, 0, 4, 0, 6\}$ ($n \to \frac{n}{2}$)


$\downarrow$ Decimated by 2

$\{1, 2, 8, 4, 6\}$

* Decimation is indeed the inverse of interpolation, but the converse is not necessarily true.


③ Time Reversal:- w.r.t imaginary axis, the given sequence is flipped off.

$x[n] \longrightarrow x[-n]$



④ Amplitude Reversal:-

$x[n] \longrightarrow -x[n]$ wrt real axis, sequence is flipped off.





Transformation on independent variable (time 'n'):-

Method-1: Shifting, Scaling, Reversal

Traverse from right to left

Ex: C.T signal : $y(t) = 5x(-2t+8)$ → T.shifting; A.S, T.R, T.scaling





$y(t) = 5x(-2t+8)$

$x(t)$

$t \to t+8$ ↓ Shifting

$x(t+8)$

$t \to 2t$ ↓ Scaling

$x(2t+8)$

$t \to -t$ ↓ Reversal


$x(-2t+8)$

↓ Amplitude Scaling


$5x(-2t+8)$


Method-2: Reversal, Scaling, Shifting

Traverse from left to right




$t \to -t$ Reversal





Shifting $t \to t-4$



Scaling $t \to 2t$

$y(t) = 5x(-2t+8)$

$= 5x(-2(t-4))$

$x(t)$ $t \to -t$ ↓ Reversal

$x(-t)$ $t \to 2t$ ↓ Scaling


$x(-2t)$ $t \to t-4$ ↓ Shifting

$x(-2(t-4))$ ↓ A.S

$5x(-2(t-4))$


Scanned by CamScanner

Pb Let $x[n] = \{1, 2, 3, 4, 5, 6\}$ (↑ at 3)




Find and sketch the following signals.

① $y_1[n] = x[n-3]$



$y_1[n] = \{0, 1, 2, 3, 4, 5, 6\}$ (↑ at 0)


② $y_2[n] = x[n+2]$



$y_2[n] = \{1, 2, 3, 4, 5, 6\}$ (↑ at 6)


③ $y_3[n] = x[-n]$

$y_3[n] = \{6, 5, 4, 3, 2, 1\}$ (↑ at 1)




④ $y_4[n] = x[-n+1]$

$y_4[n] = \{6, 5, 4, 3, 2, 1\}$ (↑ at 6)




⑤ $y_5[n] = x[-n-2]$

$y_5[n] = \{6, 5, 4, 3, 2, 1\}$ (↑ at 1)




⑥ $y_6[n] = x[2n]$

$y_6[n] = \{1, 3, 5\}$ (↑ at 5)



⑦ $y_7[n] = x[3n-1]$


$y_7[n] = \{2, 5\}$ (↑ at 5)



Scanned by CamScanner

$$x[n] \longrightarrow x\left[n - \frac{M}{N}\right]$$

what are the operations we have to perform on $x[n]$ to get $x\left[n - \frac{M}{N}\right]$



$$= x\left[n - \frac{M}{N}\right]$$

* To retain information, first do interpolation then decimation.

Pb: $x[n] = e^{-n/2}$

(1) $W[n] = 2x\left[\frac{5n}{3}\right]$

$n=0 \Rightarrow W[0] = 2x[0] = 2e^{-0} = 2$

$n=1 \Rightarrow W[1] = 2x\left[\frac{5}{3}\right] = 0$

↳ Not an integer

$n=2 \Rightarrow W[2] = 2x\left[\frac{10}{3}\right] = 0$

$n=3 \Rightarrow W[3] = 2x\left[\frac{15}{3}\right] = e^{-5/2}$

$x[n]=0$ if 'n' is not an integer

$$\therefore W[n] = 2x\left[\frac{5n}{3}\right] = \begin{cases} 2e^{-\frac{5n}{6}} & \text{'n' is multiple of '3'} \\ 0 & \text{else} \end{cases}$$

(2) $y[n] = x[2n]$

$n=0 \Rightarrow y[0] = x[0] = 1$

$n=1 \Rightarrow y[1] = x[2] = e^{-1}$

$n=2 \Rightarrow y[2] = x[4] = e^{-2}$

$n=3 \Rightarrow y[3] = x[6] = e^{-3}$

$$y[n] = x[2n] = e^{-n}$$

Scanned by CamScanner

(3) $y[n] = x[n^2]$

$n=0 \Rightarrow y[0] = x[0] = 1$

$n=1 \Rightarrow y[1] = x[1] = e^{-1/2}$

$n=2 \Rightarrow y[2] = x[4] = e^{-2}$

$\vdots$


$y[n] = x[n^2] = e^{-n^2/2}$

Basic discrete time signals / sequence :-


① Unit step signal :

$$u[n] = \begin{cases} 1 & n \geq 0 \\ 0 & n < 0 \end{cases}$$

$u[n] = \{1, 1, 1, 1, \ldots\}$ (↑ at $n=0$)




⇒ Any signal multiplied by $u[n]$ gives right-sided signal.



② Unit impulse :

$$\delta[n] = \begin{cases} 1 & n=0 \\ 0 & n \neq 0 \end{cases}$$



$\delta[n] = \{\ldots, 0, 0, 1, 0, 0, \ldots\}$ (↑ at $n=0$)

Main application: To find characterization of discrete system.

Properties of impulse function :

* i. Time scaling :

$$\boxed{\delta[kn] = \delta[n]}, \quad k \text{ is an integer}$$

Proof: $\delta[n] = \begin{cases} 1 & n=0 \\ 0 & n \neq 0 \end{cases}$

Scanned by CamScanner

$n \rightarrow kn \qquad \delta[kn] = \begin{cases} 1 & kn=0 \Rightarrow n=0 \\ 0 & kn \neq 0 \Rightarrow n \neq 0 \end{cases}$

* ii) unit impulse function $\delta[n]$ & unit step function $u[n]$ are related as

$$\boxed{\delta[n] = u[n] - u[n-1]}$$

iii) Proof: $u[n] = \begin{cases} 1 & n \geq 0 \\ 0 & n < 0 \end{cases}$

$u[n] = \{1, 1, 1, 1, \ldots\}$ $\quad u[n-1] = \{0, 1, 1, 1, 1, \ldots\}$

$u[n] = \delta[n] + \delta[n-1] + \delta[n-2] + \cdots$

$u[n] = \sum_{k=0}^{\infty} \delta[n-k] \quad , \quad u[n-1] = \sum_{k=1}^{\infty} \delta[n-k]$

$u[n] - u[n-1] = \sum_{k=0}^{\infty} \delta[n-k] - \sum_{k=1}^{\infty} \delta[n-k]$

$= \delta[n] + \sum_{k=1}^{\infty} \delta[n-k] - \sum_{k=1}^{\infty} \delta[n-k]$

$= \delta[n]$


$$\boxed{u[n] - u[n-1] = \delta[n]}$$

* iii) Multiplication property:

$$\boxed{x[n]\,\delta[n-k] = x[k]\,\delta[n-k]}$$

* iv) Unit step signal is expressed as cummulative sum of $\delta[n]$

$$\boxed{u[n] = \sum_{k=0}^{\infty} \delta[n-k]}$$



* V) Sum property:

$$\boxed{\sum_{n=-\infty}^{\infty} \delta[n] = 1}$$

Proof: $\sum_{n=-\infty}^{\infty} \delta[n] = \sum_{n=-\infty}^{-1} \delta[n] + \delta[0] + \sum_{n=1}^{\infty} \delta[n]$

$= 0 + 1 + 0$

$= 1$

Scanned by CamScanner

* Vi) Sifting property:

$$\sum_{n=-\infty}^{\infty} x[n]\,\delta[n-k] = x[k]$$

Proof: $\sum_{n=-\infty}^{\infty} x[n]\,\delta[n-k] = \sum_{n=-\infty}^{\infty} x[k]\,\delta[n-k]$ (multiplication property)

$= x[k] \sum_{n=-\infty}^{\infty} \delta[n-k]$ (Sum property $(\because = 1)$)

$= x[k]$


* Vii) Signal decomposition:

Any arbitrary signal $x[n]$ can be represented as a summation of the signal values with shifted unit impulses.

$$x[n] = \sum_{k=-\infty}^{\infty} x[k]\,\delta[n-k]$$


③ Unit Ramp signal:

$$r[n] = \begin{cases} n & n \geq 0 \\ 0 & \text{else} \end{cases}$$




$$r[n] = nu[n]$$


$u[n] = \{1, 1, 1, 1, \ldots\}$ (↑ at 0)




$u[-n] = \{\ldots, 1, 1, 1, 1\}$ (↑ at 0)



$$u[n] + u[-n] = 1 + \delta[n]$$



$u[n] - u[-n] =$



Scanned by CamScanner

$u[n] = \{1, 1, 1, \ldots\} \Rightarrow n \to 0 \text{ to } \infty$

$u[-n] = \{\ldots, 1, 1, 1\} \Rightarrow n \to -\infty \text{ to } 0$

$u[n-1] = \{0, 1, 1, \ldots\} \Rightarrow n \to 1 \text{ to } \infty$


$u[-n-1] = \{\ldots, 1, 1, 1, 0\} \Rightarrow n \to -\infty \text{ to } -1$

$u[-n+n_0] \Rightarrow n \to -\infty \text{ to } n_0$

$u[-n-n_0] \Rightarrow n \to -\infty \text{ to } -n_0$

$u[n] + u[-n-1] = 1$

$0 \text{ to } \infty \quad -\infty \text{ to } -1 \Rightarrow -\infty \text{ to } +\infty$




④ Discrete time real exponential signal:

$$x[n] = C \cdot \alpha^n \quad ; \quad -\infty < n < \infty$$


C & $\alpha \in \mathbb{R}$

Depending on 'α' values, signals are classified as

(i) if $\alpha > 1$, exponentially growing signal




(ii) if $0 < \alpha < 1$, exponentially decaying signal




Scanned by CamScanner


(iii) if $r < -1$, exponentially growing signal with alternate signs.



(iv) $-1 < r < 0$ ⇒ exponentially decaying signal with alternate signs.



⑤ Discrete time sinusoidal signals:



$$x(t)\Big|_{t=nT_s} = x(nT_s)$$

$$= \cos(2\pi f(nT_s))$$

$$= \cos\left(2\pi n \frac{f}{f_s}\right)$$

$$= \cos(2\pi n f_d)$$

T_s = Sampling interval

$f = \frac{1}{T_s}$ = Sampling frequency

$\omega = 2\pi f_d$

$\Omega = 2\pi f$

$f_d = \frac{f}{f_s}$


Analog	Digital
f (frequency)	f_d (Digital frequency)
Ω (Angular frequency)	ω (Angular digital frequency)

$$f_d \left(\frac{\text{cycles}}{\text{samples}}\right) = \frac{f}{f_s} \frac{(\text{cycles/sec})}{(\text{samples/sec})}$$

$$\omega \left(\frac{\text{radians}}{\text{sample}}\right) = \frac{\Omega}{f_s} \frac{(\text{radians/sec})}{(\text{samples/sec})} = 2\pi f_d$$

$x(t) = A\cos(2\pi f t) = A\cos(\omega t)$ → Sampling (T_s, f_s) → $x[n] = A\cos(\omega_0 n)$

Continuous → Discrete




(Pb) $x[n] = 2\cos(0.125\pi n)$

$= 2\cos\left(\frac{2\pi n}{16}\right) = A\cos(2\pi n f_d)$ $\therefore f_d = \frac{1}{16} \frac{\text{Cycles}}{\text{Samples}}$

$\Rightarrow$ **N = 16**

16 samples per one cycle



⑥ Complex exponential Signal:

Classification of Discrete time Signals:-

1. Energy and Power signals
2. Periodic and Aperiodic signals
3. Even and Odd signals
4. Summable, Square summable, absolutely summable signals.
5. Stable and unstable signals.

1. Periodic / Aperiodic signals:-

CTS

$x(t) = x(t \pm T)$

T = periodicity / Time period

$e^{j\omega_0 t}$ (complex exponential)

↳ t: may / may not be integer

$e^{j(\omega_0 + 2\pi)t} = e^{j\omega_0 t} \cdot e^{j2\pi t}$

$e^{j2\pi t}$ ↓ may / may not be '1'.

DTS

$x[n] = x[n \pm N]$

N = Time period of D.T Signal

$e^{j\omega_0 n}$ → n: Always an integer

$e^{j(\omega_0 + 2\pi)n} = e^{j\omega_0 n} \cdot e^{j2\pi n}$

$e^{j2\pi n}$ ↳ Always = 1

$= e^{j\omega_0 n}$

$$e^{j(\omega_0 + 2\pi)n} = e^{j\omega_0 n}$$

* Discrete time: complex exponential ($e^{j\omega_0 n}$) at frequency ω_0 are identical that of at $(\omega_0 \pm 2\pi), (\omega_0 \pm 4\pi), \ldots$

$x[n+N] = x[n]$

$e^{j\omega_0(n+N)} = e^{j\omega_0 n}$

$e^{j\omega_0 n} \cdot e^{j\omega_0 N} = e^{j\omega_0 n}$

$e^{j\omega_0 N} = 1$

$e^{j\omega_0 N} = e^{j2\pi m}$ → integer

$\omega_0 N = 2\pi m$

$$N = \left(\frac{2\pi}{\omega_0}\right) m$$

N → No. of samples / Time period of DTS

m → Smallest integer which makes 'N' as an integer

Scanned by CamScanner

(1) $x[n] = 5 \sin\left(\frac{3\pi}{5}\right)n$ $\quad A = 5, \quad \omega_0 = \frac{3\pi}{5}$

$N = \left(\frac{2\pi}{\omega_0}\right)m = \frac{2\pi}{3\pi/5}m = \frac{10}{3}m$

$\boxed{N = 10}$ for $m = 3$

(2) $x[n] = e^{j5\pi n}$

$N = \frac{2\pi}{5\pi}m = \frac{2}{5}m$

$m = 5 \Rightarrow \boxed{N = 2}$

(3) $x[n] = 3\sin(5n)$

$\omega_0 = 5$

$N = \frac{2\pi}{5}m$

$m = 5 \Rightarrow N = 2\pi \rightarrow$ Not an integer

Aperiodic DTS.

(4) $x[n] = x_1[n] + x_2[n] - x_3[n] + x_4[n]$

P P P P P

$\downarrow \quad \downarrow \quad \downarrow \quad \downarrow$

$\omega_{01} \quad \omega_{02} \quad \omega_{03} \quad \omega_{04}$

$\downarrow \quad \downarrow \quad \downarrow \quad \downarrow$

$N_1 \quad N_2 \quad N_3 \quad N_4$

If all signals are periodic, then $x[n]$ is periodic

$\boxed{\text{Time period } N = \text{LCM}(N_1, N_2, N_3, N_4)}$

(5) $x[n] = 4\sin\left(\frac{3\pi}{5}\right)n + 2\cos\left(\frac{5\pi}{4}\right)n - 3\sin\left(\frac{7\pi}{2}\right)n$

$\omega_{01} = \frac{3\pi}{5} \quad \omega_{02} = \frac{5\pi}{4} \quad \omega_{03} = \frac{7\pi}{2}$

$N_1 = \frac{2\pi}{3\pi/5}m_1 = \frac{10}{3}m_1 \quad N_2 = \frac{2\pi}{5\pi/4}m_2 = \frac{8}{5}m_2 \quad N_3 = \frac{2\pi}{7\pi/2}m_3 = \frac{4}{7}m_3$

$m_1 = 3 \Rightarrow N_1 = 10 \quad m_2 = 5 \Rightarrow N_2 = 8 \quad m_3 = 7 \Rightarrow N_3 = 4$

$N = \text{LCM}(N_1, N_2, N_3) = \text{LCM}(10, 8, 4)$

$2 \mid 10, 8, 4$

$2 \mid 5, 4, 2$

$5, 2, 1$

$\boxed{N = 40}$

(or)

$\omega_0 = \text{GCD}(\omega_{01}, \omega_{02}, \omega_{03}) = \text{GCD}\left(\frac{3\pi}{5}, \frac{5\pi}{4}, \frac{7\pi}{2}\right) = \frac{\text{GCD}(3\pi, 5\pi, 7\pi)}{\text{LCM}(5,4,2)}$

$= \frac{\pi}{20} \Rightarrow N = \frac{2\pi}{\pi/20}m = 40m$

$m = 1 \Rightarrow \boxed{N = 40}$

Scanned by CamScanner

(6) $x[n] = \cos^2 \frac{\pi}{4} n$

$x[n] = \frac{1 + \cos \frac{2\pi}{4}}{2} = \frac{1}{2} + \frac{1}{2} \cos \frac{\pi}{2} n$

$\omega_{01} = 2\pi, \quad \omega_{02} = \pi/2$

$N_1 = \frac{2\pi}{2\pi} m \qquad N_2 = \frac{2\pi}{\pi/2} m$

$N_1 = 1 \qquad N_2 = 4 \Rightarrow N = LCM(1, 4)$

$\boxed{N = 4}$

Problems:-

(1) $x[n] = \cos(0.01\pi n)$

$N = \frac{2\pi}{0.01\pi} m = 200m$

$\boxed{N = 200}$

(2) $x[n] = \cos\left(\pi \frac{30}{105} n\right)$

$N = \frac{2\pi}{\frac{30}{105}\pi} m = \frac{2 \times 105}{30} m$

$\boxed{N = 7}$

(3) $x[n] = \cos 3\pi n$

$N = \frac{2\pi}{3\pi} m = \frac{2}{3} m$

$\boxed{N = 2}$

(4) $x[n] = \sin 3n$

$N = \frac{2\pi}{3} \rightarrow$ Not an integer

Aperiodic DTS

(5) $x[n] = \sin\left(\frac{62\pi}{10} n\right)$

$N = \frac{2\pi}{62\pi} \times 10\, m = \frac{10}{31} m$

$\boxed{N = 10}$

(6) $x[n] = \cos(0.5n + 30^\circ)$

$N = \frac{2\pi}{0.5} \rightarrow$ Not an integer

Aperiodic DTS.

(7) $x[n] = \sin^2\left(\frac{\pi}{4} n\right)$

$x[n] = \frac{1 - \cos \frac{\pi}{2} n}{2}$

$= \frac{1}{2} - \frac{1}{2} \cos \frac{\pi}{2} n$

$N_1 = 1 \qquad N_2 = \frac{2\pi}{\pi/2} m = 4$

$N = LCM(1, 4) \Rightarrow \boxed{N = 4}$

(8) $x[n] = \cos \frac{\pi}{2} n + \sin \frac{\pi}{8} n$

$N_1 = \frac{2\pi}{\pi} (2) m = 4$

$N_2 = \frac{2\pi}{\pi} (8) m = 16$

$N = LCM(4, 16) \Rightarrow \boxed{N = 16}$

Scanned by CamScanner

(9) $x[n] = 2\cos\frac{\pi}{2}n \sin\frac{\pi}{8}n$

$= 2\cos A \sin B$

$= \sin\left(\frac{\pi}{2}+\frac{\pi}{8}\right)n - \sin\left(\frac{\pi}{2}-\frac{\pi}{8}\right)n$

$= \sin\left(\frac{5\pi}{8}\right)n - \sin\left(\frac{3\pi}{8}\right)n$

$\sin(A+B) - \sin(A-B) = 2\cos A \sin B$

$\sin(A+B) + \sin(A-B) = 2\sin A \cos B$

$\cos(A+B) + \cos(A-B) = 2\cos A \cos B$

$\cos(A-B) - \cos(A+B) = 2\sin A \sin B$

$\omega_{01} = \frac{5\pi}{8}$ $\omega_{02} = \frac{3\pi}{8}$

$N_1 = \frac{2\pi}{5\pi}(8)m$ $N_2 = \frac{2\pi}{3\pi}(8)m$

$N_1 = \frac{16}{5}m$ $N_2 = \frac{16}{3}m \Longrightarrow N = LCM\left(\frac{16}{5}, \frac{16}{3}\right)$

$N_1 = 16$ $N_2 = 16$ $\boxed{N = 16}$

2. Even and Odd signals:-

CTS	DTS	
$x(t) = x(-t)$	$x[n] = x[-n]$	$\longrightarrow$ Even
$x(t) = -x(-t)$	$x[n] = -x[-n]$	$\longrightarrow$ Odd

Note:- An odd signal must be '0' at $n=0$.

Even part of $x[n]$: $E\{x[n]\} = \frac{x[n]+x[-n]}{2}$

Odd part of $x[n]$: $O\{x[n]\} = \frac{x[n]-x[-n]}{2}$

Properties of discrete time even & Odd signals:-

1) If $x_1[n]$ is an odd signal $[x_1[n] = -x_1[-n]]$ and $x_2[n]$ is an even signal $[x_2[n] = x_2[-n]]$

(a) $x_3[n] = \overset{O}{x_1[n]}\,\overset{E}{x_2[n]} \Rightarrow$ Odd signal

(b) $x_4[n] = \overset{O}{x_1[n]} \cdot \overset{O}{x_2[n]} \Rightarrow$ Even signal

(c) $x_5[n] = \overset{E}{x_1[n]} \cdot \overset{E}{x_2[n]} \Rightarrow$ Even signal

2) If $x[n]$ is an even signal, then

$$\sum_{n=-\infty}^{\infty} x[n] = x[0] + 2\sum_{n=1}^{\infty} x[n]$$

Scanned by CamScanner

3) If $x[n]$ is an odd signal, then

$$\sum_{n=-\infty}^{\infty} x[n] = 0$$


4) If $x[n]$ is an arbitrary signal with even & odd parts denoted by $x_e[n] = E\{x[n]\}$

$x_o[n] = O\{x[n]\}$, then

$$\sum_{n=-\infty}^{\infty} x^2[n] = \sum_{n=-\infty}^{\infty} x_e^2[n] + \sum_{n=-\infty}^{\infty} x_o^2[n]$$

Pb: Determine the even & odd parts of the $x[n] = \{4, -2, 4, -6\}$

$x[n] = \{4, -2, 4, -6\} = \{4, -2, 4, -6, 0\}$



$x[-n] = \{-6, 4, -2, 4\} = \{0, -6, 4, -2, 4\}$

$x_e[n] = \frac{x[n] + x[-n]}{2} = \{2, -4, 4, -4, 2\}$


$x_o[n] = \frac{x[n] - x[-n]}{2} = \{2, 2, 0, -2, -2\}$

Pb: Find out and sketch the even & odd parts of $x[n] = u[n] - u[n-5]$

$x[n] = u[n] - u[n-5]$

$x[n] = \{1, 1, 1, 1, 1\}$


$= \{0, 0, 0, 0, 1, 1, 1, 1, 1\}$




$x[-n] = \{1, 1, 1, 1, 1\} = \{1, 1, 1, 1, 1, 0, 0, 0, 0\}$

$x_e[n] = \frac{x[n] + x[-n]}{2} = \{\frac{1}{2}, \frac{1}{2}, \frac{1}{2}, \frac{1}{2}, 1, \frac{1}{2}, \frac{1}{2}, \frac{1}{2}, \frac{1}{2}\}$

$x_o[n] = \frac{x[n] - x[-n]}{2} = \{\frac{-1}{2}, \frac{-1}{2}, \frac{-1}{2}, \frac{-1}{2}, 0, \frac{1}{2}, \frac{1}{2}, \frac{1}{2}, \frac{1}{2}\}$





Scanned by CamScanner

3. Energy & Power Signals:-

Energy of a discrete time signal → $E_x = \sum_{n=-\infty}^{\infty} |x[n]|^2$


Power of a discrete time signal ⇒ $P_x = \lim_{N\to\infty} \frac{1}{2N+1} \sum_{n=-N}^{N} |x[n]|^2$

$$\text{Power} = \frac{\text{Energy}}{\text{time}}$$

* Power is the time avg of energy.

Energy signal: if $0 < E_x < \infty$ (E_x is finite) and $P_x = 0$ } $x[n]$ = Energy sig

⇒ Signal amplitude tends to zero as $|n| \to \infty$



Power signal: if $E_x = \infty$ and $0 < P_x < \infty$ (P_x is finite) } $x[n]$ = Power sig.

→ There are signals that are neither energy nor power signals.
→ A signal can't be both energy & power signals.

Note:-

① Power is the time average of energy.: the averaging is over an infinitely large interval, a signal with finite energy has zero power and a signal with finite power has infinite energy.

∴ A signal can't be both energy & power sig.

② All practical signals have finite energy ⇒ Energy sig

③ It is impossible to generate a true power signal in practice.

$P = \frac{E}{T}$, such a signal has infinite duration & infinite energy.

④ All finite periodic signals are power signals but not all power signals are periodic

Ex:- unit step signal → Power sig

↳ but not periodic

Scanned by CamScanner

Important results:-

① $\sum_{n=0}^{\infty} a^n = \frac{1}{1-a}$; $|a| < 1$

Ex:- $1 + a + a^2 + a^3 + \cdots = \frac{1}{1-a}$

$a + ar + ar^2 + \cdots = \frac{a}{1-r}$

② $\sum_{n=0}^{N} a^n = \frac{1 - a^{N+1}}{1-a}$

③ $\sum_{n=0}^{N} (1)^n = N+1$

Ex:- $\sum_{n=0}^{2} (1)^n = 1+1+1 = 3 \Rightarrow N+1$

$2+1 = 3$

④ $\sum_{n=0}^{N} n = \frac{N(N+1)}{2}$

⑤ $\sum_{n=0}^{N} n^2 = \frac{N(N+1)(2N+1)}{6}$

⑥ $\sum_{n=0}^{N} n^3 = \left(\frac{N(N+1)}{2}\right)^2$

⑦ $\sum_{n=a}^{b} 1 = (b-a)+1$

Ex:- $\sum_{n=-2}^{2} 1 = 1+1+1+1+1 = 5$

$= (2-(-2)) + 1 = 5$

Q) Determine the values of power (P_x) and Energy (E_x) for the following signals:

(1) $x_1[n] = \left(\frac{1}{2}\right)^n u[n]$

$|x_1(n)|^2 = \left(\frac{1}{2}\right)^{2n} u^2[n] = \left(\frac{1}{4}\right)^n u[n]$

Energy: $E_x = \sum_{n=-\infty}^{\infty} |x_1[n]|^2$

$= \sum_{n=-\infty}^{\infty} \left(\frac{1}{4}\right)^n u[n]$

$\left[\because u[n] = \begin{cases} 1, & n \geq 0 \\ 0, & n < 0 \end{cases} \quad \sum_{n=0}^{\infty} a^n = \frac{1}{1-a}\right]$

$= \sum_{n=0}^{\infty} \left(\frac{1}{4}\right)^n$

$= \frac{1}{1-1/4} = \frac{4}{3}$ (finite)

Scanned by CamScanner

Power : $P_x = \lim_{N\to\infty} \frac{1}{2N+1} \sum_{n=-N}^{N} |x_1[n]|^2$

$= \lim_{N\to\infty} \frac{1}{2N+1} \sum_{n=-N}^{N} \left(\frac{1}{4}\right)^n u[n]$

$= \lim_{N\to\infty} \frac{1}{2N+1} \sum_{n=0}^{N} \left(\frac{1}{4}\right)^n$

$= \lim_{N\to\infty} \frac{1}{2N+1} \times \left[\frac{1-\left(\frac{1}{4}\right)^{N+1}}{1-\left(\frac{1}{4}\right)}\right]$

$P_x = 0$ W

$E_x = \frac{4}{3}$ J (finite)

$P_x = 0$ W

$\Big\}$ $\therefore x_1[n]$ is a energy signal.

(2) $x_2[n] = e^{j\left(\frac{\pi}{2}n + \frac{\pi}{8}\right)}$

$|x_2[n]|^2 = 1$

Energy : $E_{x_2} = \sum_{n=-\infty}^{\infty} |x_2[n]|^2$

$= \sum_{n=-\infty}^{\infty} (1)^2 = \infty$

Power : $P_{x2} = \lim_{N\to\infty} \frac{1}{2N+1} \sum_{n=-N}^{N} |x[n]|^2$

$= \lim_{N\to\infty} \frac{1}{2N+1} (N-(-N)+1)$

$= \lim_{N\to\infty} \frac{1}{2N+1} (2N+1) = 1$

$\therefore$ Power Signal with $P_x = 1$ W

(3) $x_3[n] = \cos\left(\frac{\pi}{4}n\right)$

$|x_3[n]|^2 = \cos^2\frac{\pi}{4}n = \frac{1+\cos 2\left(\frac{\pi}{4}n\right)}{2} = \frac{1}{2} + \frac{1}{2}\cos\left(\frac{\pi}{2}n\right)$

Scanned by CamScanner

$$E_x = \sum_{n=-\infty}^{\infty} |x_3[n]|^2$$

$$= \sum_{n=-\infty}^{\infty} \left(\frac{1}{2} + \frac{1}{2}\cos\frac{\pi}{2}n\right)$$

$$= \sum_{n=-\infty}^{\infty} \frac{1}{2} + \sum_{n=-\infty}^{\infty} \frac{1}{2}\cos\frac{\pi}{2}n \quad = \infty + \infty = \infty$$

$$P_x = \lim_{N\to\infty} \frac{1}{2N+1} \sum_{n=-N}^{N} |x_3[n]|^2$$

$$= \lim_{N\to\infty} \frac{1}{2N+1} \sum_{n=-N}^{N} \left(\frac{1}{2} + \frac{1}{2}\cos\frac{\pi}{2}n\right)$$

$$= \lim_{N\to\infty} \frac{1}{2N+1} \left[\frac{1}{2}(2N+1) + \frac{1}{2}(0)\right]$$

$$= \lim_{N\to\infty} \frac{1}{2}\left[\frac{2N+1}{2N+1}\right] = \frac{1}{2}$$

$\therefore$ $x_3[n]$ is a power signal with $P_x = \frac{1}{2}$ W

(4) $x_4[n] = A$

$$|x_4[n]|^2 = A^2$$

$$E_x = \sum_{n=-\infty}^{\infty} |x_4[n]|^2 = \sum_{n=-\infty}^{\infty} A^2$$

$$= A^2(\infty) = \infty$$

$$P_x = \lim_{N\to\infty} \frac{1}{2N+1} \sum_{n=-N}^{N} |x_4[n]|^2$$

$$= \lim_{N\to\infty} \frac{1}{2N+1} \sum_{n=-N}^{N} A^2$$

$$= A^2 \lim_{N\to\infty} \frac{1}{2N+1} \sum_{n=-N}^{N} (1)$$

$$= A^2 \lim_{N\to\infty} \frac{1}{2N+1} (2N+1)$$

$$= A^2 //$$

$\therefore$ $x_4[n]$ is a power signal with power A^2 W

(5) $x_5[n] = u[n]$

$|x_5[n]|^2 = u^2[n] = u[n]$

$E_x = \sum_{n=-\infty}^{\infty} |x_5[n]|^2$

$= \sum_{n=-\infty}^{\infty} u[n] = \sum_{n=0}^{\infty} 1 = \infty$

$P_x = \lim_{N\to\infty} \frac{1}{2N+1} \sum_{n=-N}^{N} |x_5[n]|^2$

$= \lim_{N\to\infty} \frac{1}{2N+1} \sum_{n=-N}^{N} u[n]$

$= \lim_{N\to\infty} \frac{1}{2N+1} \sum_{n=0}^{N} 1$

$= \lim_{N\to\infty} \frac{1}{2N+1} (N+1) = \lim_{N\to\infty} \frac{N+1}{2N+1}$ ($\because$ L-Hopital's rule)

$= \lim_{N\to\infty} \frac{1}{2} = \frac{1}{2}$

$\therefore$ Power signal with $P_x = \frac{1}{2}$ W

(6) $x_6[n] = nu[n] = n[n]$

$|x_6[n]|^2 = n^2u^2[n] = n^2u[n]$

$E_x = \sum_{n=-\infty}^{\infty} n^2u[n] = \sum_{n=0}^{\infty} n^2 = \infty$

$P_x = \lim_{N\to\infty} \frac{1}{2N+1} \sum_{n=-N}^{N} n^2u(n)$

$= \lim_{N\to\infty} \frac{1}{2N+1} \sum_{n=0}^{N} n^2$

$= \lim_{N\to\infty} \frac{1}{2N+1} \cdot \frac{N(N+1)(2N+1)}{6} = \infty$

$\therefore$ Neither Energy nor Power Signal. $E_x = \infty$, $P_x = \infty$ } NENP

$x[n] = nu[n] = n[n] \rightarrow$ NENP

(7) $x_7[n] = \delta[n]$

$|x_7[n]|^2 = \delta^2[n] = \delta[n]$

$E_x = \sum_{n=-\infty}^{\infty} \delta[n] = 1$

$P_x = \lim_{N\to\infty} \frac{1}{2N+1} \sum_{n=-N}^{N} \delta[n]$

$= \lim_{N\to\infty} \frac{1}{2N+1} (1) = \frac{1}{\infty} = 0$

∴ Energy signal with $E_x = 1$ J

(8) $x[n] = \begin{cases} n, & 0 \le n \le 5 \\ 0 & \text{else} \end{cases}$

$E_x = \sum_{n=-\infty}^{\infty} n^2 = \sum_{n=0}^{5} n^2 = \frac{5(5+1)(2(5)+1)}{6}$

$= \frac{5 \times 6 \times 11}{6} = 55$ J

$P_x = \lim_{N\to\infty} \frac{1}{2N+1} \sum_{n=-N}^{N} n^2$

$= \lim_{N\to\infty} \frac{1}{2N+1} \sum_{n=0}^{5} n^2 = \frac{1}{\infty} \times 55 = 0$

∴ Energy signal with $E_x = 55$ J

Note:- All finite length signals/sequences are Energy Signals.

(9) Consider the discrete time signal $x[n] = \delta[n+2] - \delta[n-2]$

Calculate E_y for $y[n] = \sum_{k=-\infty}^{\infty} x[k]$

Given, $x[n] = \delta[n+2] - \delta[n-2]$

$y[n] = \sum_{k=-\infty}^{\infty} x[k]$

$x[k] = \delta[k+2] - \delta[k-2]$

$y[n] = \sum_{k=-\infty}^{\infty} \delta[k+2] - \delta[k-2]$


Scanned by CamScanner

$$y[n] = \sum_{k=-\infty}^{\infty} \delta[k+2] = \sum_{k=-\infty}^{\infty} \delta[k-2]$$

$$y[n] = u[n+2] - u[n-2]$$

$\downarrow$ -2 to $+2$

$$= \begin{cases} 1 & -2 \le n \le 1 \\ 0 & \text{otherwise} \end{cases}$$



Energy : $E_y = \sum_{n=-\infty}^{\infty} |y[n]|^2$

$$= \sum_{n=-2}^{1} 1 = (1+2)+1$$

$$= 4\,J \Longrightarrow \boxed{\text{Energy} : E_y = 4\,J}$$

Power : $P_y = \lim_{N\to\infty} \frac{1}{2N+1} \sum_{n=-N}^{N} (1)$

$$= \lim_{N\to\infty} \frac{1}{2N+1} \sum_{n=-2}^{1} (1) = \frac{1}{\infty} = 0$$

(10) $x[n] = j^{n/4}$

$$x[n] = e^{\frac{jn\pi}{2}\cdot\frac{1}{4}} = e^{\frac{j\pi}{8}n} \left[j = e^{\frac{j\pi}{2}} \right]$$

$$j^{n/4} = e^{\frac{j\pi}{2}\left(\frac{n}{4}\right)} = e^{\frac{j\pi}{8}n} \therefore$$

$$|x[n]|^2 = 1$$

Energy : $E_x = \sum_{n=-\infty}^{\infty} 1 = \infty$

Power : $\lim_{N\to\infty} \frac{1}{2N+1} \sum_{n=-N}^{N} (1) = \lim_{N\to\infty} \frac{1}{2N+1} (2N+1) = 1$

$\therefore$ Power signal with $P_x = 1\,W$

(11) $x[n] = (\sqrt{j})^n + (\sqrt{j})^{-n}$ $\left[j = e^{\frac{j\pi}{2}} \right]$

$$x[n] = j^{n/2} + j^{-n/2}$$

$$= e^{jn\pi/4} + e^{-jn\pi/4} = 2\cos\left(\frac{\pi}{4}n\right)$$

Scanned by CamScanner

Power : $P_x = \lim_{N\to\infty} \frac{1}{2N+1} \sum_{n=-N}^{N} \left(2\cos\frac{\pi}{4}n\right)^2$

$= \lim_{N\to\infty} \frac{1}{2N+1} \sum_{n=-N}^{N} \left[4\cos^2\frac{\pi}{4}n\right]$

$= \lim_{N\to\infty} \frac{1}{2N+1} \sum_{n=-N}^{N} \left[4^2\left(\frac{1+\cos 2\left(\frac{\pi}{4}n\right)}{2}\right)\right]$

$= \lim_{N\to\infty} \frac{1}{2N+1} \sum_{n=-N}^{N} \left(2+2\cos\frac{\pi}{2}n\right)$

$= \lim_{N\to\infty} \frac{1}{2N+1} \sum_{n=-N}^{N} 2 + \lim_{N\to\infty} \frac{1}{2N+1} \sum_{n=-N}^{N} 2\cos\frac{\pi}{2}n$

$= \lim_{N\to\infty} \frac{1}{2N+1} 2(2N+1) + \lim_{N\to\infty} \frac{1}{2N+1} 2(0)$

$P_x = \underline{2W}$

Energy : $E_x = \sum_{n=-\infty}^{\infty} \left(2+2\cos\frac{\pi}{2}n\right)$

$= \infty$

∴ Power signal with $\underline{P_x = 2W}$

4. Conjugate Symmetric / Anti-Symmetric Signals :-

Conjugate Symmetric Signals	Conjugate Anti-Symmetric Signals
$\boxed{x[n] = x^*[-n]}$ $\forall n$	$\boxed{x[n] = -x^*[-n]}$ $\forall n$
⇒ A real conjugate symmetric signal is said to be even sig. $x[n] = x[-n]$	⇒ A real conjugate Anti-Symmetric sig is said to be odd sig. $x[n] = -x[-n]$

Scanned by CamScanner

Complex discrete time signal : $x[n] = x_{cs}[n] + x_{cA}[n]$

$$x_{cs}[n] = \frac{x[n] + x^*[-n]}{2} \qquad x_{cAs}[n] = \frac{x[n] - x^*[-n]}{2}$$

$$x_e[n] = \frac{x[n] + x[-n]}{2} \qquad x_o[n] = \frac{x[n] - x[-n]}{2}$$

Q) $x[n] = \{0,\ 1+j4,\ -2+j3,\ 2-j4,\ -6-j5,\ 7,\ -j3\}$
↑

$$x_{cs}[n] = \frac{x[n] + x^*[-n]}{2} \qquad x_{cAs}[n] = \frac{x[n] - x^*[-n]}{2}$$

$x[-n] = \{-j3,\ 7,\ -6-j5,\ 2-j4,\ -2+j3,\ 1+j4,\ 0\}$
↑


$x^*[-n] = \{j3,\ 7,\ -6+j5,\ 2+j4,\ -2-j3,\ 1-j4,\ 0\}$
↑

$x_{cs}[n] = \{j1.5,\ 4+j2,\ -4+j4,\ 2,\ -4-j4,\ 4-j2,\ -j1.5\}$
↑

$x_{cAs}[n] = \{-j1.5,\ -3+j2,\ 2-j,\ -j4,\ -2-j,\ 3+j2,\ -j1.5\}$
↑

5. **Bounded Signals:-**

A discrete time signal $x[n]$ is said to be bounded if each of its samples is of magnitude less than or equal to a finite +ve number B_x i.e., $|x[n]| < B_x < \infty$



Ex:- $u[n]$ is bounded sig with $B_x = 1$.

6. **Summable / Square Summable Signals:-**


Absolutely Summable sig's: A DTS is said to be absolutely summable if and only if $\sum_{n=-\infty}^{\infty} |x(n)| < \infty$ → finite value

Square Summable sig:- A DTS is said to be sss if & only if $\sum_{n=-\infty}^{\infty} |x[n]|^2 < \infty$


* sss has finite energy, $P=0 \Rightarrow$ Energy sig.

Scanned by CamScanner

Discrete time systems :-



Physical entity which is characterized by its ability to accept inputs - Voltage, current, pressure, force, displacement.



$T\{\cdot\} \Rightarrow$ Transformation operation / System operation.

$$y[n] = T\{x[n]\}$$

Classification of Systems :- → Based on how the system interacts with the input signals "MODELS"


1. Linear / Non-linear Systems
2. Time varient / Time invarient systems.
3. Memory less / with memory systems.
4. Static / Dynamic systems
5. Causal / Non-causal systems
6. Stable / Unstable systems.

1. Linear / Non-linear Systems :-

Linear System : A system which possesses the important property of superposition.

Superposition principle : The response resulting from several input signals can be computed as the sum of the responses resulting from each input signal acting alone.

Scanned by CamScanner



$x_1[n] \longrightarrow y_1[n]$

$x_2[n] \longrightarrow y_2[n]$

$x_1[n] + x_2[n] \longrightarrow y_1[n] + y_2[n]$

① The response to $\{x_1[n] + x_2[n]\}$ is $\{y_1[n] + y_2[n]\}$ → Additivity property

② The response to $a \cdot x[n]$ is $a \cdot y[n]$ → Scaling / Homogenity property

a: arbitrary constant

① + ② ⇒ Superposition principle


$$\{a \cdot x_1[n] + b \cdot x_2[n]\} \longrightarrow \{a \cdot y_1[n] + b\, y_2[n]\}$$

Superposition ⇒ [Additivity + Homogenity] ⇒ Linear system

Note:- * Zero input → Zero output ✓

Q) For each of the following i/p-o/p relationship, determine whether the following systems are linear / Non-linear.

(a) $y[n] = n\,x[n]$



$x[n] = \{2, 1, -3, 1, 4\}$
↑

$y[n] = \{0, 1, -6, 3, 16\}$
↑

n	x[n]	y[n] = n x[n]
0	2	0 x[0] = 0x2 = 0
1	1	1 x[1] = 1x1 = 1
2	-3	2 x[2] = 2x-3 = 6
3	1	3 x[3] = 3x1 = 3
4	4	4 x[4] = 4x4 = 16

Consider two arbitrary signals,

$x_1[n] \longrightarrow y_1[n] = n\,x_1[n]$

$x_2[n] \longrightarrow y_2[n] = n\,x_2[n]$

$x_3[n] \longrightarrow y_3[n] = n\,x_3[n]$

Let x_3 be linear combination of $x_1[n]$ & $x_2[n]$

$$x_3[n] = a\,x_1[n] + b\,x_2[n]$$

a & b are arbitrary constants

Scanned by CamScanner

LHS : $y_3[n] = x_3[n] \cdot x_3[n-1]$

$= (a x_1[n] + b x_2[n]) \cdot (a x_1[n-1] + b x_2[n-1])$

$= a^2 x_1[n] x_1[n-1] + ab x_1[n] x_2[n-1] + ab x_2[n] x_1[n-1] + b^2 x_2[n] x_2[n-1]$

$\neq$ RHS

$\therefore$ LHS $\neq$ RHS

So, the given system is non-linear system.

Q) For the system described by the following difference equation with the input $x[n]$ and output $y[n]$, determine which of the systems are linear / Non-linear.

Note:- A difference equation is non-linear, if a constant term is present or a term contains the product of the input and/or output.

(a) $y[n] - 2y[n-1] = 4x[n]$

$x_1[n] \longrightarrow y_1[n]$	$y_1[n] - 2y_1[n-1] = 4x_1[n] \rightarrow ①$
$x_2[n] \longrightarrow y_2[n]$	$y_2[n] - 2y_2[n-1] = 4x_2[n] \rightarrow ②$
$x_3[n] \longrightarrow y_3[n]$	$y_3[n] - 2y_3[n-1] = 4x_3[n] \rightarrow ③$

Multiplying ① x a & ② x b and then add ① a + ② b

$a y_1[n] - 2a y_1[n-1] = 4a x_1[n]$

$b y_2[n] - 2b y_2[n-1] = 4b x_2[n]$

$a y_1[n] + b y_2[n] - 2a y_1[n-1] - 2b y_2[n-1] = 4a x_1[n] + 4b x_2[n]$

$= 4[a x_1[n] + b x_2[n]]$

$= 4 (x_3[n])$

$\therefore$ Linear System.

$y[n] - 2y[n-1] = 4x[n]$

$x_3[n] = a x_1[n] + b x_2[n]$, $y_3[n] = a y_1[n] + b y_2[n]$

Scanned by CamScanner

(b) $y[n] - 3n\,y[n-1] = x[n]$

$x_1[n] \rightarrow y_1[n]$ | $y_1[n] - 3n\,y_1[n-1] = x_1[n] \rightarrow ①$

$x_2[n] \rightarrow y_2[n]$ | $y_2[n] - 3n\,y_2[n-1] = x_2[n] \rightarrow ②$

$x_3[n] \rightarrow y_3[n]$ | $y_3[n] - 3n\,y_3[n-1] = x_3[n] \rightarrow ③$

Let x_3 be linear combination of x_1 & x_2,

$$x_3[n] = ax_1[n] + bx_2[n], \quad y_3[n] = ay_1[n] + by_2[n]$$

$① \times a + ② \times b \Rightarrow ay_1[n] - 3an\,y_1[n-1] + by_2[n] - 3bn\,y_2[n-1] = ax_1[n] + bx_2[n]$

$$ay_1[n] + by_2[n] - 3n\left[ay_1[n-1] + by_2[n-1]\right] = x_3[n]$$

$$y_3[n] - 3n\,y_3[n-1] = x_3[n]$$

Hence proved $\rightarrow ③$

∴ Given system is Linear.

(c) $y[n] + 2y^2[n] = x[n]$

$x_1[n] \rightarrow y_1[n]$ | $y_1[n] + 2y_1^2[n] = x_1[n] \rightarrow ①$

$x_2[n] \rightarrow y_2[n]$ | $y_2[n] + 2y_2^2[n] = x_2[n] \rightarrow ②$

$x_3[n] \rightarrow y_3[n]$ | $y_3[n] + 2y_3^2[n] = x_3[n] \rightarrow ③$

Let x_3 be linear combination of x_1 & x_2,

$$x_3[n] = ax_1[n] + bx_2[n], \quad y_3[n] = ay_1[n] + by_2[n]$$

$① \times a + ② \times b \rightarrow ay_1[n] + 2ay_1^2[n] + by_2[n] + 2by_2^2[n] = ax_1[n] + bx_2[n]$

Scanned by CamScanner

(d) $y[n] - ay[n-1] = a^{x[n]} \cdot x[n]$

$x_1[n] \longrightarrow y_1[n]$	$y_1[n] - ay_1[n-1] = a^{x_1[n]} \cdot x_1[n] \longrightarrow ①$
$x_2[n] \longrightarrow y_2[n]$	$y_2[n] - ay_2[n-1] = a^{x_2[n]} \cdot x_2[n] \longrightarrow ②$
$x_3[n] \longrightarrow y_3[n]$	$y_3[n] - ay_3[n-1] = a^{x_3[n]} x_3[n] \longrightarrow ③$

Let $x_3[n] = ax_1[n] + bx_2[n]$, $y_3[n] = ay_1[n] + by_2[n]$

$① \times a + ② \times b \Rightarrow ay_1[n] - a^2 y_1[n-1] + by_2[n] - a^2 by_2[n-1] = a \cdot a^{x_1[n]} \cdot x_1[n] + b a^{x_2[n]} \cdot x_2[n]$

$\underbrace{ay_1[n] + by_2[n]}_{y_3[n]} - a\underbrace{(ay_1[n-1] + by_2[n-1])}_{y_3[n-1]} = a a^{x_1[n]} \cdot x_1[n] + b a^{x_2[n]} \cdot x_2[n]$

$y_3[n] - ay_3[n-1] = a a^{x_1[n]} x_1[n] + b x_2[n] a^{x_2[n]}$

LHS $\neq$ RHS ($\because$ From -③)

$\therefore$ Given system is non-linear.

(e) $y[n] + a^n y[n-1] = x[n]$

$x_1[n] \longrightarrow y_1[n]$	$y_1[n] + a^n y_1[n-1] = x_1[n] \longrightarrow ①$
$x_2[n] \longrightarrow y_2[n]$	$y_2[n] + a^n y_2[n-1] = x_2[n] \longrightarrow ②$
$x_3[n] \longrightarrow y_3[n]$	$y_3[n] + a^n y_3[n-1] = x_3[n] \longrightarrow ③$

Let $x_3[n] = ax_1[n] + bx_2[n]$, $y_3[n] = ay_1[n] + by_2[n]$

$① \times a + ② \times b \Rightarrow ay_1[n] + a a^n y_1[n-1] + by_2[n] + ba^n y_2[n-1] = ax_1[n] + bx_2[n]$

$\underbrace{ay_1[n] + by_2[n]}_{y_3[n]} + \underbrace{(ay_1[n-1] + by_2[n-1])}_{y_3[n-1]} a^n = x_3[n]$

$y_3[n] + a^n y_3[n-1] = x_3[n]$

LHS = RHS (Hence proved -③)


$\therefore$ Given system is Linear.

Scanned by CamScanner


2. **Time variant / Time invariant Systems:-**
(shift varient) (shift invarient)


⇒ A system is time invariant, if the behaviour and characteristics of the system is fixed over time.

⇒ A system is said to be time invariant, if a time shift in the input signal causes an identical time shift in the output signal.




⇒ Time invariant System






If $x[n] \longrightarrow y[n]$

$x[n-n_0] \longrightarrow y[n-n_0]$

① 

② 

⇒ If the output is same in both processes, then the system is said to be time-invariant.

Q) For each of the following i/p-o/p relationships, determine whether the corresponding systems is time variant / invariant [TI].

(a) $y[n] = nx[n]$

Scanned by CamScanner

① Shift in i/p by n_0 $\Rightarrow$ $y[n-n_0] = nx[n-n_0]$

② Shift in o/p by n_0 $\Rightarrow$ $y[n-n_0] = (n-n_0)x[n-n_0]$

$x[n] \rightarrow y[n]$

$x[n-n_0] \rightarrow y[n-n_0]$


① $\neq$ ② $\rightarrow$ Time variant System.

(b) $y[n] = x[-n]$

① Shift in i/p $\Rightarrow$ $y[n-n_0] = x[-n-n_0]$

② Shift in o/p $\Rightarrow$ $y[n-n_0] = x[-(n-n_0)] = x[-n+n_0]$

① $\neq$ ② $\rightarrow$ TV system



(c) $y[n] = x[2n]$

① Shift in i/p $\Rightarrow$ $y[n-n_0] = x[2n-n_0]$

② Shift in o/p $\Rightarrow$ $y[n-n_0] = x[2(n-n_0)] = x[2n-2n_0]$

① $\neq$ ② $\rightarrow$ TV system.

Note:-

① A difference equation belongs to a time varying system if a coefficient is an explicit function of time (n) or a scaled input or output [Ex: $y[2n]$ or $x[\frac{n}{2}]$ is present]

② A difference equation belongs to a linear and time-invariant system (LTI) if all the coefficients are constants and no constant terms are present.

Q) For the system described by the difference equation. TV (or) TI

(a) $y[n] - 2y[n-1] = 4x[n]$

Since all the coefficients are constant, this difference equation belongs to Time invariant system.

Scanned by CamScanner

(b) $y[n] - 3n\,y[n-1] = x[n]$

↓ explicit function of n ⟹ so, time variant system.

(c) $y[n] + 2y^2[n] = 2x[n]$

↓ 1 ; ↓ 2 ; ↓ 2

All coefficients are constants ⟹ so, TI system.

(d) $y[n] - 2y[n-1] = 2^{x[n]} \cdot x[n]$ ⟹ Time invariant system.


(e) $y[n] + 2^n y[n-1] = x[n]$

↳ Explicit function of n ⟹ so, time variant system.

3. Causal and Non-causal Systems :-

↳ Non-anticipating system → Physically realizable systems.

⟹ A system is said to be causal if the output at any time, (to) 'n₀' depends only on the values of the input at the present and in the past.



Q) For each of the following i/p-o/p relationship, determine whether the corresponding system is causal or non-causal.

(a) $y[n] = nx[n]$

n	y[n]
-2	-2x[-2]
-1	-x[-1]
0	0x[0]
1	1x[1]
2	2x[2]

Output depends on present values of input.

Causal System

(b) $y[n] = x[-n]$

$y[0] = x[0]$ → Present ; $y[-1] = x[1]$ → Future

$y[\phi] = x[-1]$ → Past ∴ Non-causal system.

Scanned by CamScanner

(c) $y[n] = x[2n]$

$y[0] = x[0]$ → Present — So, non-Causal system.

$y[1] = x[2]$ → Future

(d) $y[n] = x[n]\{\cos(n+1)\}$ → Causal System

4. Systems with memory and without memory :-

with memory → dynamic system

without memory → Static system.

Dynamic system: If its o/p signal depends on past or future values of the input signals

o/p = f[past or future inputs]

Static System: If its o/p signal depends only on the present value of input signal.

o/p = f[Present input values only]

Ex:- ① $y[n] = 5x[n]$ → Static system

② $y[n] = 2x(n) + 9x^2[n]$ → Static system


③ $y[n] = \sum_{k=-\infty}^{n} x[k]$ → Dynamic System

↳ Accumulator System (or) Summar system

④ $y[n] = x[n-1]$ → Dynamic System, depends on past values

↳ Delay system

5. Invertible / Non-invertible Systems :-



S_1 : Invertible system S_2 : Inverse system.

Scanned by CamScanner

* If the system has inverse system, then it is invertible system otherwise non-invertible.


* Inverse system "undoes" what the given system [S] does to input.

⇒ For a system to have an inverse (or to be invertible), distinct input must lead to distinct outputs.


⇒ If a system produces identical output for two different inputs, it does not have an inverse.

⇒ For an invertible system, it is essential that every input have a unique output.

⇒ One to one mapping b/w input & output.



Ex: $y[n] = \cos(x[n])$ $\quad x[n] + 2\pi k$, $k = 0, \pm1, \pm2, \pm3 \ldots\ldots$




$$\cos(x[n]) = \cos(x[n] + 2\pi k)$$

$y[n] = \cos[x(n)] \Rightarrow$ Non-invertible system

$\because \cos(x[n]) = \cos(x(n)+2\pi)$
$= \cos(x(n)-2\pi)$

Bcoz different i/p's yield an identical output

Invertible LTI Systems ⇒ difference equation



Difference equ of LTI Is ⇒ $y[n] = x[n] - 0.5x[n-1]$

Difference equ of Inverse ⇒ $x[n] = y[n] - 0.5y[n-1]$

switching input with output

6. Stable / Unstable Systems:-

A stable system is the one in which small inputs leads to response that do not diverge.

Bounded input ⟶ Bounded output

(BIBO stability)

⇒ A system is said to be BIBO stable if and only if, for every bounded input results in a bounded o/p.

$$|x[n]| < B_x < \infty \quad \forall n$$

$$|y[n]| < B_y < \infty$$

$$|x[n]| < B_x \leq \infty \implies |y[n]| < B_y < \infty$$

Analysis on Discrete time Systems :-

- Physical phenomenon
- Mathematical analysis (easy)

- Solving difference equ by applying some specific inputs & with initial conditions.
- Impulse response
- represent any arbitrary signal in terms of time shifted impulses.
- Based on this compute the output of the given system.

* Any physical phenomenon in terms of LTI systems.
* Mathematical analysis is easy on LTI systems.


So, that's why we use LTI systems for discrete time system analysis.

Primary reasons:

⇒ LTI systems are amenable to analysis is that any such system possesses the superposition principle.

⇒ We can represent the input to an LTI system in terms of a linear combination of a set of basic signals.

∴ Output of the system could be computed as sum of individual responses.



Analysis ⇒ Determining the response to some specified input

Solve the difference equ describing the system subjected to the specified i/p's & with initial conditions.

By characterizing an LTI system in terms of impulse response, defined as the o/p of an LTI system due to unit impulse sig applied at n=0.


Scanned by CamScanner

Now, given the impulse response, we determine the response of an LTI system due to arbitrary signal by expressing the i/p as a weighted superposition of time shifted impulses.

⇒ By linearity and time invariance, the o/p signal must be a weighted superposition of time shifted impulse responses.

↳ CONVOLUTION sum of discrete time LTI system

→ Impulse response




impulse i/p signal — Impulse response

$$x[n] \longrightarrow y[n]$$

$$\delta[n] \longrightarrow h[n]$$

Ex:



$$x[n] = ax_1[n] + bx_2[n] \longrightarrow y[n] = ay_1[n] + by_2[n]$$


$$x[n] = a_1x_1[n] + a_2x_2[n] + a_3x_3[n] + \dots + a_Nx_N[n]$$

$$y[n] = a_1y_1[n] + a_2y_2[n] + a_3y_3[n] + \dots + a_Ny_N[n]$$

Input $\boxed{x[n] = \sum_{i=1}^{N} a_i x_i[n]}$

Output $\boxed{y[n] = \sum_{i=1}^{N} a_i y_i[n]}$

Ex:-



$x[n] = \{2, -1, 1, 2, 1\}$ (↑ at $x[1]$)


$x[-2] = 2$

$x[-1] = -1$

$x[0] = 2$

$x[1] = 2$

$x[2] = 1$



$$x[n] = x[-2]\delta[n+2] + x[-1]\delta[n+1] + x[0]\delta[n] + x[1]\delta[n-1] + x[2]\delta[n-2]$$

$$\therefore x[n] = \sum_{k=-2}^{+2} x[k]\,\delta[n-k]$$

If $x[n] \longrightarrow y[n]$

$\delta[n] \longrightarrow h[n]$

$\delta[n-k] \longrightarrow h[n-k]$ $\Rightarrow$ This is because of time invariance

$x[k]\,\delta[n-k] \longrightarrow x[k]\,h[n-k]$ $\Rightarrow$ Coz of scaling


$$\sum_{k=-\infty}^{\infty} \underbrace{x[k]\,\delta[n-k]}_{=x[n]\ (i/p)} \longrightarrow \sum_{k=-\infty}^{\infty} \underbrace{x[k]\,h[n-k]}_{=y[n]\ (o/p)}$$ $\Rightarrow$ Coz of Linearity

So, the response or output of an LTI system

$$y[n] = \sum_{k=-\infty}^{\infty} x[k]\,h[n-k]$$ $\Rightarrow$ Convolution Sum of D.T LTI Systems.

$$y[n] = x[n] * h[n]$$

Scanned by CamScanner



$$y[n] = x[n] * h[n] = \sum_{k=-\infty}^{\infty} x[k]\, h[n-k]$$

For $x[n] = 0$, $n < k_1$ (function of n)

$x[k] = 0$, $k < k_1$ (function of k)

$h[n] = 0$, $n < k_2$ (function of n)

$h[n-k] = 0$, $n-k < k_2$

$k > n - k_2$

So, $y[n] = x[n] * h[n] = \sum_{k=k_1}^{n-k_2} x[k]\, h[n-k]$; $n \geq k_1 + k_2$

($n - k_2 - k_1 \geq 0$, $n \geq k_1 + k_2$)

$y[n] = 0$; $n < k_1 + k_2$

Q) Find the convolution of two sequences, $x[n] = \begin{cases} 0 & n < -5 \\ \left(\frac{1}{2}\right)^n & n \geq -5 \end{cases}$

$h[n] = \begin{cases} 0 & n < 3 \\ \left(\frac{1}{3}\right)^n & n \geq 3 \end{cases}$

Here, $k_1 = -5$, $k_2 = 3$

we know that, $y[n] = x[n] * h[n]$; $n \geq k_1 + k_2 = -5 + 3 = -2$

$y[n] = 0$; $n < k_1 + k_2$

$n < -5 + 3 = -2 \Rightarrow n < -2$

$$y[n] = \sum_{k=k_1}^{n-k_2} x[n]\, h[n-k] = \sum_{k=-5}^{n-3} \left(\frac{1}{2}\right)^k \left(\frac{1}{3}\right)^{n-k} \quad ; \; n \geq -2$$

$$y[n] = \sum_{k=-5}^{n-3} \left(\frac{1}{2}\right)^k \left(\frac{1}{3}\right)^{n-k} \quad ; \; n \geq -2$$

A change of variables is performed by letting $m = k + 5$, $k = m - 5$

As $k = -5 \Rightarrow m = -5 + 5 = 0$

As $k = n - 3 \Rightarrow m = n - 3 + 5 = n + 2$

$$\therefore y[n] = \sum_{m=0}^{n+2} \left(\frac{1}{2}\right)^{m-5} \left(\frac{1}{3}\right)^{n-m+5}$$

Scanned by CamScanner

$$y[n] = \left(\frac{2}{3}\right)^5 \left(\frac{1}{3}\right)^n \sum_{m=0}^{n+2} \left(\frac{3}{2}\right)^m$$

$$= \left(\frac{2}{3}\right)^5 \left(\frac{1}{3}\right)^n \sum_{m=0}^{n+2} \left(\frac{3}{2}\right)^m$$

$$= \left(\frac{2}{3}\right)^5 \left(\frac{1}{3}\right)^n \left[\frac{\left(\frac{3}{2}\right)^0 - \left(\frac{3}{2}\right)^{n+2+1}}{1-\frac{3}{2}}\right] \qquad \left(\because \sum_{n=0}^{N} a^n = \frac{1-a^{N+1}}{1-a}\right)$$

$$= -2\left(\frac{2}{3}\right)^5 \left(\frac{1}{3}\right)^n \left[1 - \left(\frac{3}{2}\right)^{n+3}\right]$$

$$= -2\left(\frac{2}{3}\right)^5 \left[\left(\frac{1}{3}\right)^n - \left(\frac{1}{2}\right)^n \left(\frac{3}{2}\right)^3\right]$$

$$y[n] = -64\left(\frac{1}{3}\right)^{n+5} + 2\left(\frac{2}{3}\right)^2 \left(\frac{1}{2}\right)^n \quad ; n+n \geq -2$$

Computation of convolution sum

- Analytical method
- Graphical method

Graphical method:-

$$y[n] = \sum_{k=-\infty}^{\infty} x[k]\, h[n-k]$$

1. Plotting: First plot $x[k]$ & $h[k]$ as a function of 'k' [not 'n'] bcoz summation is wrt 'k'.

$x[n] \rightarrow x[k]$; $h[n] \rightarrow h[k]$

2. Shifting: Shift $h[k]$ by 'n' units to obtain $h[k+n]$

$h[k] \rightarrow h[k+n]$

3. Folding: Invert $h[k+n]$ about vertical axis [k=0 axis] to obtain $h[-k+n] = h[n-k]$

$h[k+n] \rightarrow h[-k+n]$

4. Multiplication & Addition: Next multiply $x[k]$ & $h[n-k]$ and add all the products to obtain $y[n]$.

This procedure is repeated for each value of $n \Rightarrow -\infty$ to $+\infty$

Scanned by CamScanner

Q) Compute the convolution of sequences $y[n] = x[n] * h[n]$


(a) $x[n] = u[n]$; $h[n] = u[n]$

We know that, $y[n] = x[n] * h[n] = \sum_{k=-\infty}^{\infty} x[k]\, h[n-k]$


$$y[n] = \sum_{k=-\infty}^{\infty} u[k]\, u[n-k] \rightarrow \text{function of } k.$$

①


$$u[n] = \begin{cases} 1 & n \geq 0 \\ 0 & n < 0 \end{cases}$$



$$u[k] = \begin{cases} 1 & k \geq 0 \\ 0 & k < 0 \end{cases}$$




② Shifting: $u[k] \rightarrow u[k+n]$




$$u[k+n] = \begin{cases} 1 & k+n \geq 0 \Rightarrow k \geq -n \\ 0 & k+n < 0 \Rightarrow k < -n \end{cases}$$

③ Folding, $u[k+n] \longrightarrow u[-k+n] = u[n-k] = \begin{cases} 1 & -\infty < k < n \\ 0 & k > n \end{cases}$



④ Multiply & add : $u[k]\, u[n-k] = \begin{cases} 1 & 0 \leq k \leq n \\ 0 & k < 0 \\ & k > n \end{cases}$



Summation

$$y[n] = \sum_{k=-\infty}^{\infty} u[k] \cdot u[n-k] = \sum_{k=0}^{n} 1$$

$$= (n+1), \quad n \geq 0$$

$$y[n] = \begin{cases} n+1 & ; n \geq 0 \\ 0 & n < 0 \end{cases} = (n+1)\, u[n] \Rightarrow y[n] = (n+1)u[n]$$

$$\boxed{y[n] = r[n+1]}$$

Scanned by CamScanner

So, $u[n] * u[n] = (n+1)\,u[n]$

$$\boxed{u[n] * u[n] = r[n+1]}$$

$n \cdot u[n] = r[n]$

$(n+1)\,u[n+1] = (n+1)\,u[n]$

$= r[n+1]$

(b) $x[n] = (0.8)^n u[n]$, $h[n] = (0.4)^n u[n]$

$$y[n] = x[n] * h[n] = \sum_{k=-\infty}^{\infty} x[k]\, h[n-k]$$

$$= \sum_{k=-\infty}^{\infty} (0.8)^k u[k] \cdot (0.4)^{n-k} u[n-k]$$

$$= (0.4)^n \sum_{k=0}^{n} (0.8)^k (0.4)^{-k}$$

$$= (0.4)^n \sum_{k=0}^{n} \left(\frac{0.8}{0.4}\right)^k = (0.4)^n \sum_{k=0}^{n} 2^k$$

$$= (0.4)^n \left[\frac{1-2^{n+1}}{1-2}\right] \quad \therefore y[n] = \underline{\underline{\left[2(0.8)^n - (0.4)^n\right]}}\, u[n]$$

$$\therefore y[n] = (0.4)^n \left[2^{n+1} - 1\right] = \left[2(0.8)^n - (0.4)^n\right] \; ; n \geq 0$$

(c) $x[n] = h[n] = a^n u[n]$

$$y[n] = x[n] * h[n] = \sum_{k=-\infty}^{\infty} x[k]\, h[n-k]$$

$$= \sum_{k=-\infty}^{\infty} a^k u[k] \cdot a^{n-k} u[n-k]$$

$$= \sum_{k=0}^{n} a^k \cdot a^{n-k}$$

$$= \sum_{k=0}^{n} a^n = a^n \sum_{k=0}^{n} 1 = a^n (n+1) \; ; n \geq 0$$

$$y[n] = \begin{cases} a^n (n+1) & ; n \geq 0 \\ 0 & n < 0 \end{cases}$$

$$y[n] = \underline{\underline{a^n (n+1) \cdot u[n]}}$$

Scanned by CamScanner

(d) $x[n] = u[n-1]$ $\quad h[n] = \alpha^n u[n-1]$

$$y[n] = x[n] * h[n] = \sum_{k=-\infty}^{\infty} x[k]\, h[n-k]$$

$$= \sum_{k=-\infty}^{\infty} u[k-1] \cdot \alpha^{n-k} u[n-k-1]$$

$$u[k-1] = \begin{cases} 1 & k-1 \geq 0 \Rightarrow k \geq 1 \\ 0 & k-1 < 0 \Rightarrow k < 1 \end{cases} \qquad u[n-k-1] = \begin{cases} 1 & n-k-1 \geq 0 \\ & k \leq n-1 \\ 0 & k > n-1 \end{cases}$$

$$\therefore y[n] = \sum_{k=1}^{n-1} \alpha^{n-k}$$

$n-k-1 \geq 0 \quad | \quad n-k-1 < 0$

$n-1 \geq k \quad | \quad n-1 < k$

$k \leq n-1 \quad | \quad k > n-1$

$$= \alpha^n \sum_{k=1}^{n-1} \left(\frac{1}{\alpha}\right)^k$$

Change of variables

$\Rightarrow m = k-1$

$k=1 \Rightarrow m=0$

$k=n-1 \Rightarrow m = n-2$

$$= \alpha^n \sum_{m=0}^{n-2} \left(\frac{1}{\alpha}\right)^{m+1}$$

$$= \alpha^{n-1} \sum_{m=0}^{n-2} \left(\frac{1}{\alpha}\right)^m$$

$$= \alpha^{n-1} \left[\frac{1 - \left(\frac{1}{\alpha}\right)^{n-2+1}}{1 - \left(\frac{1}{\alpha}\right)} \right]$$

$$= \alpha^{n-1} \left[\frac{1 - \left(\frac{1}{\alpha}\right)^{n-1}}{1 - \left(\frac{1}{\alpha}\right)} \right] = \frac{\alpha^{n-1} - \alpha^{n-1} \frac{1}{\alpha^{n-1}}}{1 - \frac{1}{\alpha}} = \frac{\alpha^n - \alpha}{\alpha - 1}$$

(e) $x[n] = r[n] = nu[n]$; $h[n] = a^{-n} u[n-1]$; $a < 1$

$$y[n] = x[n] * h[n] = \sum_{k=-\infty}^{\infty} x[k]\, h[n-k]$$

$$= \sum_{k=-\infty}^{\infty} ku[k] \cdot a^{-(n-k)} u[n-k-1]$$

$$u[k] = \begin{cases} 1 & k \geq 0 \\ 0 & k < 0 \end{cases} \qquad u[n-k-1] = \begin{cases} 1 & n-k-1 \geq 0 \\ & k \leq n-1 \\ 0 & k > n-1 \end{cases}$$

Scanned by CamScanner

$$y[n] = \sum_{k=0}^{n-1} k a^{-n+k}$$

$$= a^{-n} \sum_{k=0}^{n-1} k a^{k}$$

$$= \frac{a}{(1-a)^2} \left[1 - n a^{n-1} + (n-1) a^{n}\right] \cdot a^{-n}$$

Proof:-

$$\sum_{k=0}^{n-1} k a^{k} = S = 0 + a + 2a^2 + 3a^3 + \cdots + (n-2)a^{n-2} + (n-1)a^{n-1} + 0$$

$$aS = 0 + a^2 + 2a^3 + 3a^4 + \cdots + (n-2)a^{n-1} + (n-1)a^{n}$$

$$S - aS = \underbrace{a + a^2 + a^3 + a^4 + \cdots + a^{n-2} + a^{n-1}}_{\hookrightarrow n-1 \text{ terms}} - (n-1)a^{n}$$

$$S(1-a) = \frac{a(1-a^{n+1})}{1-a} - (n-1)a^{n}$$

$$S = \frac{a(1-a^{n+1})}{(1-a)^2} - \frac{(n-1)a^{n}}{(1-a)}$$

$$= \frac{a(1-a^{n+1}) - (n-1)(1-a)a^{n}}{(1-a)^2}$$

$$= \frac{a - a^{n} - \left[(n-1)(a^{n} - a^{n+1})\right]}{(1-a)^2}$$

$$= \frac{a - a^{n} - \left[n a^{n} - a^{n} - n a^{n+1} + a^{n+1}\right]}{(1-a)^2}$$

$$= \frac{a - a^{n} - n a^{n} + a^{n} + n a^{n+1} - a^{n+1}}{(1-a)^2} = \frac{a - n a^{n} + n a^{n+1} - a^{n+1}}{(1-a)^2}$$

$$\sum_{k=0}^{n-1} k a^{k} = S = \frac{a(1 - n a^{n-1} + n a^{n} - a^{n})}{(1-a)^2} = \frac{a}{(1-a)^2}\left[1 - n a^{n-1} + (n-1)a^{n}\right]$$

Scanned by CamScanner

Q) Suppose the unit impulse response of an LTI system is a unit ramp, $h[n] = r[n] = nu[n]$. Compute the response of the system to the unit step input, $x[n] = u[n]$

Given, $x[n] = u[n] = \begin{cases} 1 & n \geq 0 \\ 0 & n < 0 \end{cases}$

$h[n] = nu[n] = \begin{cases} n & n \geq 0 \\ 0 & n < 0 \end{cases}$

We know that, $y[n] = x[n] * h[n] = \sum_{k=-\infty}^{\infty} x[k]\, h[n-k]$

$= \sum_{k=-\infty}^{\infty} u[k] \cdot (n-k)\, u[n-k]$

$u[k] = \begin{cases} 1 & k \geq 0 \\ 0 & k < 0 \end{cases}$ $\quad u[n-k] = \begin{cases} 1 & n-k \geq 0 \Rightarrow k \leq n \\ 0 & k > n \end{cases}$

Then, $y[n] = \sum_{k=0}^{n} 1\,(n-k)\,; n \geq 0 \quad (\because u[k]\,u[n-k] = 1 \text{ for } 0 \text{ to } n)$

$= n + (n-1) + (n-2) + \cdots + 3 + 2 + 1 + 0 = \frac{n(n+1)}{2}$

$\therefore y[n] = \begin{cases} \frac{n(n+1)}{2} & n \geq 0 \\ 0 & n < 0 \end{cases}$

Note:-

① If $x[n] = \delta[n]$, $y[n] = h[n]$ → Impulse response

② If $x[n] = u[n]$, $y[n] = s[n]$ → Unit step response


Scanned by CamScanner

Properties of convolution sum:-

1. Commutative property:

$$x[n] * h[n] = h[n] * x[n]$$

$$\sum_{k=-\infty}^{\infty} x[k]\, h[n-k] = \sum_{k=-\infty}^{\infty} h[k]\, x[n-k]$$



Proof:- By definition, we know that

$$x[n] * h[n] = \sum_{k=-\infty}^{\infty} x[k]\, h[n-k]$$

By change of variables, Let $n-k = m$

$$k = n-m$$

As $k = -\infty \Rightarrow m = \infty$

$k = +\infty \Rightarrow m = -\infty$

$$x[n] * h[n] = \sum_{m=\infty}^{-\infty} x[n-m]\, h[m]$$


$$= \sum_{m=-\infty}^{\infty} h[m] \cdot x[n-m]$$

$$y[n] = h[n] * x[n]$$

∴ Convolution sum obeys commutative law.

2. Associative property:


$$x[n] * [h_1[n] * h_2[n]] = [x[n] * h_1[n]] * h_2[n]$$



↳ They get convolved

3. Distributive property:

$$x[n] * [h_1[n] + h_2[n]] = x[n] * h_1[n] + x[n] * h_2[n]$$



If two systems are parallel → they get added.

4. Shift property:

If $x[n] * h[n] = y[n]$

then $x[n] * h[n-n_0] = y[n-n_0]$

(or)

then $x[n-n_0] * h[n] = y[n-n_0]$

or)

then $x[n-n_1] * h[n-n_2] = y[n-n_1-n_2]$

5. Impulse convolution property:

Convolution of a signal $x[n]$ with a unit impulse signal results in the signal $x[n]$ itself.

$$x[n] * \delta[n] = x[n]$$

6. Sum property:

The sum of the impulses in a convolution, sum of two discrete time sequences is the product of the sum of the impulses in the two individual sequences.

Let the sum of all the impulses in the signals $y[n]$, $x[n]$ and $h[n]$ be S_y, S_x and S_h respectively.

$$\therefore S_y = \sum_{n=-\infty}^{\infty} y[n] \quad S_x = \sum_{n=-\infty}^{\infty} x[n], \quad S_h = \sum_{n=-\infty}^{\infty} h[n]$$

Scanned by CamScanner

then, $\sum_{n=-\infty}^{\infty} y[n] = \sum_{n=-\infty}^{\infty} x[n] \cdot \sum_{n=-\infty}^{\infty} h[n]$

$$\boxed{S_y = S_x \cdot S_h}$$

Q) Show that

(a) The convolution of an odd signal and an even signal is an odd signal.

Let $x[n]$ be an odd signal,

$$x[n] = -x[-n]$$

Let $h[n]$ be an even signal,

$$h[n] = h[-n]$$

Then, $y[n] = \sum_{k=-\infty}^{\infty} -x[-n] \cdot h[-n-k]$

$$y[n] = x[n] * h[n]$$

$$= -x[-n] * h[-n]$$

$$= -\{x[-n] * h[-n]\} = -\{y[-n]\}$$

$$y[n] = -y[-n] \Rightarrow \text{Odd signal.}$$

(b) The convolution of two odd signals is an even signal.

Let $x[n]$ and $h[n]$ be odd signals,

$$x[n] = -x[-n] \qquad h[n] = -h[-n]$$

$$y[n] = x[n] * h[n]$$

$$= -x[-n] * -h[-n]$$

$$= x[-n] * h[-n] = y[-n] \longrightarrow \text{Even signal}$$

$$y[n] = y[-n]$$

(c) The convolution of two even signals is even signal.

Let $x[n]$ & $h[n]$ are two even signals

$$x[n] = x[-n], \quad h[n] = h[-n]$$

Scanned by CamScanner

$x[n] * h[n] = x[-n] * h[-n]$

$y[n] = y[-n]$ → Even signal.

Q) Prove the following

(1) $x[n] * \delta[n-n_0] = x[n-n_0]$

By definition, $x[n] * \delta[n-n_0] = \sum_{k=-\infty}^{\infty} x[k]\,\delta[n-n_0-k]$

By multiplication property of impulse function,

$$x[n]\,\delta[n-k] = x[k]\,\delta[n-k]$$

then $x[k]\,\delta[n-n_0-k] = x[n-n_0]\,\delta[n-n_0-k]$

By this property,

$$x[n] * \delta[n-n_0] = \sum_{k=-\infty}^{\infty} x[n-n_0]\,\delta[n-n_0-k]$$

$$= x[n-n_0] \underbrace{\sum_{k=-\infty}^{\infty} \delta[n-n_0-k]}_{=1}$$

$$\boxed{x[n] * \delta[n-n_0] = x[n-n_0]}$$

Hence proved.

(2) $x[n] * \delta[n+n_0] = x[n+n_0]$

By definition, $x[n] * \delta[n+n_0] = \sum_{k=-\infty}^{\infty} x[k]\,\delta[n+n_0-k]$

By multiplication property,

$$x[n]\,\delta[n-k] = x[k]\,\delta[n-k]$$

then $x[k]\,\delta[n+n_0-k] = x[n+n_0]\,\delta[n+n_0-k]$

By this property,

$$x[n] * \delta[n+n_0] = \sum_{k=-\infty}^{\infty} x[n+n_0]\,\delta[n+n_0-k]$$

$$= x[n+n_0] \underbrace{\sum_{k=-\infty}^{\infty} \delta[n+n_0-k]}_{=1}$$

$= x[n+n_0]$ // Hence proved.

Scanned by CamScanner

(3) $x[n] * u[n] = \sum_{k=-\infty}^{n} x[k]$

By definition $\Rightarrow$ $x[n] * u[n] = \sum_{k=-\infty}^{\infty} x[k]\,u[n-k]$

$$u[n-k] = \begin{cases} 1 & ; \ n-k \geq 0 \Rightarrow k \leq n \\ 0 & \ n-k < 0 \Rightarrow k > n \end{cases}$$

$$x[n] * u[n] = \sum_{k=-\infty}^{n} x[k]\,\underbrace{u[n-k]}_{=1}$$

$$= \sum_{k=-\infty}^{n} x[k] \quad //$$ Hence proved

(4) $u[n] * u[n] = (n+1)\,u[n]$

By definition $\Rightarrow$ $u[n] * u[n] = \sum_{k=-\infty}^{\infty} u[k]\,u[n-k]$

$$u[k] = \begin{cases} 1 & k \geq 0 \\ 0 & k < 0 \end{cases} \qquad u[n-k] = \begin{cases} 1 & n-k \geq 0 \Rightarrow k \leq n \\ 0 & n-k < 0 \Rightarrow k > n \end{cases}$$

So, 1 for limits : 0 to n

$$u[n] * u[n] = \sum_{k=0}^{n} u[k]\,u[n-k]$$

$$= \sum_{k=0}^{n} (1) = \begin{cases} n+1 & ; \ n \geq 0 \\ 0 & ; \ n < 0 \end{cases}$$

$$u[n] * u[n] = \begin{cases} n+1 & ; \ n \geq 0 \\ 0 & \ n < 0 \end{cases} = (n+1)\,u(n) \quad //$$ Hence proved.

CONVOLUTION SUM OF FINITE LENGTH SIGNALS:

$x[n]$, $h[n]$ } Finite in length then $y[n]$ = finite

$x[n] = \{\underset{\uparrow}{1}, 2, 3, 4, 5\}$ Length of $x(n)$ = 5 samples

$h[n] = \{\underset{\uparrow}{-1}, 3, 2, -2, 7, 6, 2\}$ Length of $h[n]$ = 7 samples

Scanned by CamScanner

LE_x → left end of x LE_h → left end of h

RE_x → Right end of x RE_h → Right end of h

$LE_x = 0$ $LE_h = 0$

$RE_x = 4$ $RE_h = 6$

Length of $y[n]$ = No. of samples in $x[n]$ + No. of samples in $h[n]$ − 1

$= 5 + 7 - 1 = 11$

$LE_y = LE_x + LE_h = 0 + 0 = 0$

$RE_y = RE_x + RE_h = 4 + 6 = 10$

Methods:-

① Tabulation method to compute convolution sum of finite length sequence

② Multiplication method " " " "

1. Tabulation method :- $x[n] = \{1, 2, 3, 4, 5\}$

$h[n] = \{1, 1, 1, 1\}$

h[n] \ x[n]	1	2	3	4	5
1	1x1 = 1	1x2 = 2	1x3 = 3	1x4 = 4	1x5 = 5
1	1	2	3	4	5
1	1	2	3	4	5
1	1	2	3	4	5

$y[n] = \{1, 1+2, 1+2+3, 1+2+3+4, 2+3+4+5, 3+4+5, 4+5, 5\}$

$y[n] = \{1, 3, 6, 10, 14, 12, 9, 5\}$

Scanned by CamScanner

Length of $y[n]$ = Samples of $x(n)$ + Samples of $h[n]$ − 1

$= 5 + 4 - 1 = 8$

	LE	RE
$x(n)$	0	4
$h(n)$	0	3
$y(n)$	0	7

$x[n] = LE_x, RE_x$, $h[n] = LE_h, RE_h$

$y[n] \Rightarrow LE_y = LE_x + LE_h$

$RE_y = RE_x + RE_h$

Q) $x[n] = \{\overset{\uparrow}{2}, -1, 3\}$ $h[n] = \{\overset{\uparrow}{1}, 2, 2, 3\}$

$LE_x = 0$ $LE_h = 0$ then $LE_y = 0 + 0 = 0$

$RE_x = 2$ $RE_h = 3$ $RE_y = 2 + 3 = 5$

Length of $y[n] = 3 + 4 - 1$

$= 7 - 1 = 6$ samples

$h[n]$ \ $x[n]$	2	−1	+3
1	2	−1	+3
2	4	−2	+6
2	4	−2	+6
3	6	−3	+9

$y[n] = \{2, 4-1, 4-2+3, 6-2+6, -3+6, 9\}$

$y[n] = \{2, 3, 5, 10, 3, 9\}$ (0 1 2 3 4 5)

Sum property:- $S_y = S_x \cdot S_h$

$S_y = \sum_{n=-\infty}^{\infty} y[n]$, $S_h = \sum_{h=-\infty}^{\infty} h[n]$, $S_x = \sum_{n=-\infty}^{\infty} x[n]$

$x(n) = \{2, -1, 3\} \rightarrow S_x = 2 - 1 + 3 = 4$

$h[n] = \{1, 2, 2, 3\} \Rightarrow S_h = 1 + 2 + 2 + 3 = 8$

$y[n] = \{2, 3, 5, 10, 3, 9\} \Rightarrow S_y = 2 + 3 + 5 + 10 + 3 + 9 = 32$

$S_y = S_x \cdot S_h$

$S_y = 4 \cdot 8 = \underline{32}$

Scanned by CamScanner

2. Multiplication method:

$x[n] = \{4, 5, 6\}$ $h[n] = \{4, 4, 3, 2\}$

$LE_x = 0$ $LE_h = 0$ then $LE_y = 0 + 0 = 0$

$RE_x = 2$ $RE_h = 3$ $RE_y = 2 + 3 = 5$

Length of $y[n]$ = Samples in $x[n]$ + Samples in $h[n]$ -1

$= 3 + 4 - 1 = 6$ samples

$x[n]$ 4 4 3 2

$h[n]$ X 4 5 6

	24	24	18	12
16	16	15	10	X
16	16	12	8	X
16	36	56	47	28	12

$\therefore y[n] = \{16, 36, 56, 47, 28, 12\}$

System response to periodic inputs:-

The response of a discrete time system to a periodic input with period N is also periodic with the same period N. $x[n] = x[n+N]$ → periodicity

Proof:-

$x[n]$ → $h[n]$ → $y[n] = x[n] * h[n]$

Using time shifting property of the convolution,

$y[n+N] = x[n+N] * h[n]$

→ $x[n]$ be periodic with period N.

$x[n] = x[n+N]$

$y[n+N] = \underbrace{x[n] * h[n]}_{= y[n]}$

$\therefore \boxed{y[n+N] = y[n]}$ $\therefore$ The response is also periodic with period 'N'.

Ex: $x[n] = \{\overbrace{2, 1, -3}, \overbrace{2, 1, -3}, \overbrace{2, 1, -3}, \ldots_{\infty}\}$
$\uparrow$

$h[n] = \{1, 1\}$
$\uparrow$

Find the convolution sum of $x[n]$ and $h[n]$ using multiplication method.

$x[n] \rightarrow LEx = 0$, $REx = \infty$ $\quad h[n] \rightarrow LEh = 0$, $REh = 1$

Output: $y[n] \rightarrow LEy = 0+0 = 0$
$REy = \infty + 1 = \infty$

So, $y[n]$ starts at origin and ends at ∞.

By multiplication method,

$x[n]$ 2 1 −3 2 1 −3 2 1 −3 ..... $n=\infty$

$h[n]$

2 1 −3 2 1 −3 2 1 −3 ..... $n=\infty$

2 1 −3 +2 +1 −3 +2 +1 −3 X ..... $n=\infty$

2 3 −2 −1 3 −2 −1 3 −2 ..... $n=\infty$

$\therefore y[n] = \{\underbrace{2}_{\text{Startup effect}}, \underbrace{3, -2, -1}, \underbrace{3, -2, -1}, \underbrace{3, -2, \ldots}_{n=\infty}\}$
$\uparrow$

$\rightarrow$ Except the value at origin, the response $y[n]$ is periodic with period $\underline{N=3}$

Scanned by CamScanner

Q) Let $x[n] = \{2, 1, -3, 2, 1, -3, 2, 1, -3, \ldots\}$
$\uparrow$

$h[n] = \{1, 1, 1\}$
$\uparrow$ Find the convolution sum by multiplication method?

$x[n] \longrightarrow LE_x = 0$, $RE_x = \infty$; $h[n] \longrightarrow LE_h = 0$, $RE_h = 2$; then $y[n] \longrightarrow LE_y = 0+0 = 0$, $RE_y = \infty + 2 = \infty$

$x[n]$ 2 1 -3 2 1 -3 2 1 -3 ...

$h[n]$ x 1 1 1

2 1 -3 2 1 -3 2 1 -3

~~1 -3 2 1 -3~~ x

2 1 -3 2 1 -3 2 1 -3 ....

2 1 -3 2 1 -3 2 1 -3 .....

2 3 0 0 0 0 0 0 0 -2 -3 .....

Moving average system

Q) Let $x_p[n] = \{2, 1, -3\}$ described by one period with input $x[n]$ with period $N = 3$ to the system whose impulse response is given as $h[n] = \{1, 1\}$. Determine $y[n]$ for one period.
$\uparrow$

$y_1[n] = x_p[n] * h[n]$

$= \{2, 1, -3\} * \{1, 1\}$

$= \{2, 3, -2, -3\} \rightarrow$ Length = 4
$\uparrow$

2 1 -3 x
1 1
2 1 -3
2 1 -3
2 3 -2 -3

$x_p \Longrightarrow N = 3$ 2 3 -2

-3

$y_p[n] =$ -1 3 -2

So, $y_p[n] = \{-1, 3, 2\} \rightarrow$ period $N = 3$

Scanned by CamScanner

$x_p[n] = \{2, 1, -3\}$ → $h[n] = \{1, 1\}$ → $y_p[n] = \{-1, 3, -2\}$

$x[n] = \{2, 1, -3, 2, 1, -3, \dots\}$ $\quad y[n] = \{-1, 3, -2, -1, 3, -2 \dots\}$

Note:- If i/p is periodic, o/p is also periodic

If i/p having a period of N then output also have period N = 3.

Q) $x_p[n] = \{1, 2, 3\}$ (one period of i/p), $x[n] = \{1, 2, 3, 1, 2, 3, \dots\}$ (i/p to the system), $h[n] = \{1, 1, 2, -1, 2\}$ (Impulse response of system.)

Periodicity of N = 3

$y_1[n] = x_p[n] * h[n]$

$= \{1, 2, 3\} * \{1, 1, 2, -1, 2\}$

1	1	2	-1	2
		1	2	3
3	3	6	-3	6
2	2	4	-2	4
1	1	2	-1	2
1	3	7	6	6	1	6

$\Rightarrow y_1[n] = \{1, 3, 7, 6, 6, 1, 6\}$

↑ Length = 7

$x_p \rightarrow N=3$ $\quad 1 \;\; 3 \;\; 7 \;|\; 6 \;\; 6 \;\; 1 \;|\; 6$

1	3	7
6	6	1
6		
13	9	8

$\rightarrow y_p[n] = \{13, 9, 8\}$

$x_p[n] = \{1, 2, 3\}$ → $h[n] = \{1, 1, 2, -1, 2\}$ → $y_p[n] = \{13, 9, 8\}$ with N = 3

$x[n] = \{1, 2, 3, 1, 2, 3, \dots\}$ $\quad y[n] = \{13, 9, 8, 13, 9, 8, \dots\}$

Scanned by CamScanner

Relationship b/w LTI systems properties and impulse response

① LTI systems with memory and without memory

Dynamic — static

$h[n]$ → impulse response

⇒ A DTS is said to be memoryless if and only if the impulse response $\boxed{h[n] = k\delta[n]}$ $k = h[0]$ ↳ constant

⇒ If a DTS has an impulse response $h[n]$ that is not identically zero for $n \neq 0$ then that system has memory.

$h[n] \neq 0$ for $n \neq 0$

② Causality for LTI system

⇒ A DTS is said to be causal if and only if $h[n] = 0$ for $n < 0$


$\boxed{h[n] = 0 \;;\; n < 0}$ (past)

③ Stability of an LTI system

⇒ A DTS is said to be stable if and only if its impulse response is absolutely summable.

i.e, $\boxed{\sum_{n=-\infty}^{\infty} |h[n]| < \infty}$ (finite)

④ Invertability for LTI system



$\boxed{h[n] * h_I[n] = \delta[n]}$

Property conditions for impulse response

1. Memoryless — $h[n] = k\delta[n]$
2. Causality — $h[n] = 0$ for $n < 0$
3. Stability — $\sum_{n=-\infty}^{\infty} |h[n]| < \infty$ (finite)
4. Invertibility — $h[n] * h_I[n] = \delta[n]$

Q) Consider a DTS with impulse response $h[n] = \alpha^n u[n]$. Determine whether the system is causal and/or stable.

Given, $h[n] = \alpha^n u[n] = \begin{cases} \alpha^n ; & n \geq 0 \\ 0 & n < 0 \end{cases}$

Causal: $h[n] = 0$ for $n < 0 \Rightarrow$ System is causal.

Stable: $\sum_{n=-\infty}^{\infty} |h[n]| \leq \infty \Rightarrow \sum_{n=-\infty}^{\infty} |\alpha^n u[n]|$

$$= \sum_{n=-\infty}^{\infty} |\alpha^n| \, |u[n]|$$

$$\sum_{n=0}^{\infty} |\alpha^n| = \frac{1}{1-|\alpha|}, \quad |\alpha| < 1$$

If $|\alpha| < 1$, Let $\alpha = 0.5$ so, $\frac{1}{1-|\alpha|} = \frac{1}{1-|0.5|} = 2$ (finite) (bounded)

when $|\alpha| < 1$, the system will be stable.

If $|\alpha| = 1 \Rightarrow \frac{1}{1-|\alpha|} = \frac{1}{1-1} = \frac{1}{0} = \infty$ (unbounded)


when $|\alpha| = 1$, the system is unstable.

$|\alpha| < 1 \rightarrow$ Stable

$|\alpha| = 1 \rightarrow$ unstable

Scanned by CamScanner

UNIT STEP RESPONSE OF LTI SYSTEM



$y[n] = x[n] * h[n] \Rightarrow y[n] = u[n] * h[n]$

$$= \sum_{k=-\infty}^{\infty} h[k]\, u[n-k]$$

$$u[n-k] = \begin{cases} 1 & ; k \le n \\ 0 & k > n \end{cases}$$

$$= \sum_{k=-\infty}^{n} h[k]$$

$$\therefore y[n] = s[n] = \sum_{k=-\infty}^{n} h[k]$$

$$s[n] = h[n] + \underbrace{\sum_{k=-\infty}^{n-1} h[k]}_{s[n-1]}$$

$$\boxed{\begin{aligned} s[n] &= h[n] + s[n-1] \\ h[n] &= s[n] - s[n-1] \end{aligned}}$$

⇒ The step response of a DTS is the running sum of its impulses.

⇒ Conversely, the impulse response of a DTS is the first difference of its step response.


Q) Let $s[n]$ be the step response of a DTS. Show that the response $y[n]$ to the input $x[n]$ is given by

$$y[n] = [x[n] - x[n-1]] * s[n]$$

$$= x[n] * [s[n] - s[n-1]]$$

Scanned by CamScanner

Difference Equations: → Linear, constant coefficient difference equation (LCCDE).



$$y[n] = f\{x[n], x[n-1], x[n-2], \ldots x[n-M], y[n-1], y[n-2], \ldots y[n-N]\}$$

$$y[n] = -\sum_{k=1}^{N} a_k y[n-k] + \sum_{l=0}^{M} b_l x[n-l]$$

$$\sum_{k=0}^{N} a_k y[n-k] = \sum_{l=0}^{M} b_l x[n-l]$$

⟹ Order of diff. equation: ORDER = Max [N, M]

⟹ Difference equation is said to be "NON-RECURSIVE"

if $a_k = 0$ for $k \neq 0$

Output y[n] is only defined in terms of the input signals.

⟹ NON-RECURSIVE systems are said to be FINITE LENGTH IMPULSE RESPONSE (FIR) system.

⟹ A difference equation is said to be "RECURSIVE" when y[n] includes weighted versions of the earlier outputs i.e., y[n] may be defined in terms of y[n-1], y[n-2], y[n-3], ...

⟹ RECURSIVE systems are said to be INFINITE LENGTH IMPULSE RESPONSE (IIR) system.

Causal LTI systems:-

→ Use difference equation as algorithm to find y[n] from x[n]

→ Initial conditions must be initial rest.

If $x[n] = 0$ for $n < n_0$ then $y[n] = 0$ for $n \leq n_0$

Then we call it as causal LTI system.

Ex:- $y[n] - a\,y[n-1] = bx[n]$ (diff equ)

$y[n] - ay[n-1] = bx[n]$


This is RECURSIVE diff equ: Bcoz y[n] is defined in terms of y[n-1]

ORDER: Max [N, M] ⟹ $\left.\begin{matrix} M = 0 \\ N = 1 \end{matrix}\right\}$ Order = 1

Note:- Max delay which exists in a given diff equation = order.

Scanned by CamScanner

Q) Find $h[n]$ for causal LTI system from diff equation:



$$y[n] = a\,y[n-1] + b\,x[n]$$

$$h[n] = a\,h[n-1] + b\,\delta[n]$$

($h[n]=0$, $n<0$ for causal)

Initial rest $\Rightarrow$ $h[n]=0$ for $n<0$ bcoz $x[n]=0$ for $n<0$

$n=0 \Rightarrow$ $h[0] = a\underbrace{h[0-1]}_{=0} + b\underbrace{\delta[0]}_{=1}$

$$h[0] = 0 + b = b$$

$n=1 \Rightarrow$ $h[1] = a\underbrace{h[1-1]}_{=b} + b\underbrace{\delta[1]}_{=0}$

$$h[1] = ab$$

$n=2 \Rightarrow$ $h[2] = a\underbrace{h[2-1]}_{=ab} + b\underbrace{\delta[2]}_{=0}$

$$h[2] = a^2b$$

$$\therefore h[n] = \begin{cases} a^n b & n \geq 0 \\ 0 & n<0 \end{cases}$$

Q) $y[n] = \frac{1}{2}x[n-1] + \frac{1}{2}x[n-2]$

This is NON-RECURSIVE diff. equation : Bcoz $y[n]$ depends only on values of input

ORDER: Max [1,2] = 2 (max delay)

Use diff eqn to find $h[n]$ for causal LTI system;


$$y[n] = \frac{1}{2}x[n-1] + \frac{1}{2}x[n-2]$$

$x[n] \longrightarrow y[n]$

$\delta[n] \rightarrow h[n]$

$$h[n] = \frac{1}{2}\delta[n-1] + \frac{1}{2}\delta[n-2]$$

$$h[n] = \{0, \underset{\uparrow}{\frac{1}{2}}, \frac{1}{2}\}$$




Scanned by CamScanner

BLOCK DIAGRAM:


LCCDE : $\sum_{k=0}^{N} a_k y[n-k] = \sum_{l=0}^{M} b_l x[n-l]$

sum, Scaling element, delay, Sum, Scaling element, delay


① ADDER:



② Multiplier / scalar / Gain :



③ Delay :




Ex:-(1) $y[n] - ay[n-1] = bx[n]$

$y[n] = ay[n-1] + bx[n]$

$x[n] \longrightarrow y[n]$

$\delta[n] \Longrightarrow h[n]$

$h[n] = ah[n-1] + b\delta[n]$



Block diagram.


* When feedback path occurs, it is a RECURSIVE system & IIR system.


② $y[n] = \frac{1}{2}x[n-1] + \frac{1}{2}x[n-2]$

* NON-RECURSIVE system as it has no feedback path.

FIR system.

Scanned by CamScanner





Aperiodic signal
- CT - continuous time fourier transform
- DT - Discrete time fourier transform

Discrete time fourier series:-

Def:- Fourier series is a mathematical tool that allows representation of any periodic signal as the sum of harmonically related complex exponential signals

Periodic : $x(t) = x(t + mT_0)$ $m \rightarrow$ any integer

$T_0 \rightarrow$ Smallest value (fundamental period)

Fundamental frequency : $\omega_0 = \frac{2\pi}{N}$ rad/samples

$x(n) = \{e^{j\omega_0 n}, e^{j2\omega_0 n}, e^{j3\omega_0 n}, \ldots, e^{jk\omega_0 n}\}$

Periodic signal with fund. frequency $= \omega_0$

$x(n) = \sum_{k=<N>} X_k e^{jk\omega_0 n}$

$X_k =$ arbitrary constant